

KNAUF

Armstrong Bioguard® Plain RH99



*Protection from specific strains of bacteria





















Armstrong BIOGUARD® PLAIN offers anti-microbial and anti-mold performance to assist with infection control.

- Anti-microbial and anti-mold performance to assist with infection control*
- Appealing smooth surface
- Wipeable surface: Ceiling Tiles can be directly cleaned with damp cloth
- Healthcare zones like ICU, small surgery zones, radiology rooms, laboratories, kitchens, food service and processing areas, etc

Build on us.

Armstrong Bioguard® Plain RH99

Characteristic	Detailed information		
Edge details 	Board 	Tegular 24/90 	Tegular 15/90 
Thickness (mm) 	16	16	16
Dimensions (mm) 	600 x 600 600 x 1200	600 x 600 600 x 1200	600 x 600 600 x 1200
System 	Exposed Grid System, Demountable Ceiling (Prelude 24 mm)		Exposed Grid System, Demountable Ceiling (Suprafine 15 mm / Silhouette)
Weight 	≅ 3.6 kg/m²		
Colour 	 White		
Sound attenuation 	CAC = 35 dB		
Fire Reaction 	Class 0 / Class 1 as per BS 476 Pt - 6 & 7 Class A as per ASTM E-84		
Light reflectance 	Up to 90%		
Thermal conductivity 	$\lambda = \mathbf{0.052 - 0.057 W/mK}$		
Humidity resistance 	Up to 99% RH		
Recycled content 	Up to 34%		
Cleanability 			
Sustainability 