

## GUARDEX<sup>®</sup> Screw MU

Technical Data Sheet 12/2023



## GUARDEX<sup>®</sup> Screw MU

Hanger element

### Product Description

Guardex<sup>®</sup> self-drilling screws with countersunk cross-heads, having exposed to min. 240 hrs of salt test, are for fixing Guardex<sup>®</sup> to metal substructure with thickness of 1 mm up to 3 mm.

### Storage

- Direct contact with water should be avoided.
- Packages should be stored in flat, dry and clean areas.

### Referans Standart

-

### Fields of Application

- Guardex<sup>®</sup> Exterior Drywall System with ETICS
- Guardex<sup>®</sup> Exterior Drywall Lining System with ETICS
- Guardex<sup>®</sup> Ventilated Façade System

### Properties

- Clean and easy installation.

### Technical Data

Description	Diameter (mm)	Length (mm)	Weight (kg/box)	Packaging Unit (pcs./pallet)	Material Number
GUARDEX® Screw MU	3,5	25	1,5	1000	449550

### System Performance Values

Performance values as sound insulation, fire resistance etc. may differ acc. to the drywall system to be applied. Please check the performance values of the drywall systems;

[Knauf Technical Website](#)  
[Document Center](#)

### Application

Application should be done acc. to the applicable standards (TS 1475) and acc. to the Knauf Technical Brochures of the respective drywall system.

▶ 444 YAPI - 9274

▶ [www.knauf.com.tr](http://www.knauf.com.tr) / [www.teknik.knauf.com.tr](http://www.teknik.knauf.com.tr)

▶ [teknik@knauf.com](mailto:teknik@knauf.com)

Center: Knauf Moment Beştepe Office, Beştepe Mah. 32.Cadde No:1/212-218 06560 Beştepe-Yenimahalle / ANKARA Tel: 0312 297 0100 Faks: 0312 266 4506