



USGKnauf EasyJoint® JOINTING COMPOUND


USGKnauf EasyJoint® is a setting type compound used for treating Gypsum board joints and fixing points.

EasyJoint® provides excellent tape bonding strength, is exceptionally smooth to work with and the easy mixing saves time. EasyJoint® has a consistent setting time and is relatively easy to sand, giving a high level of finish.

Product Usage Data:

Setting Time	180 minutes
Mixing Ratio	2 parts of compound to 1 part of clean water (in kg.)
Coverage	One bag can cover approximately 65sqm.
Storage	The product must be kept in dry conditions, away from moisture. The bag should be stored at an elevated position. Part open bags should be sealed, as moisture can accelerate the setting time.

Mixing Procedure:




1. Always use clean water, tools and containers. Using dirty containers / tools may affect setting time.



2. Slowly add powder to water and mix for 2-3 minutes.


Tapered Edge Joints (3 easy steps):

1st Coat




Apply EasyJoint® of 150 mm width for joint reinforcement.

2nd Coat




Apply an even coat of EasyJoint® of 200 mm width.

3rd Finishing Coat




Apply an even coat of EasyJoint® of 300 mm width for finishing.


Square Edge Joints (3 easy steps):



Apply EasyJoint® of 300 mm width for joint reinforcement.



Apply an even coat of EasyJoint® of 400 mm width.



Apply an even coat of EasyJoint® of 500-600 mm width for finishing.

Note: All Gypsum board joints require light sanding before painting.

* Available in 20kg bag

Knauf India Private Limited

Head Office: 9th Floor, Plaza Tower, DLF Phase -1, Gurugram - 122002, Haryana, India

Customer Care No: +91 - 9015147147

Email: info.india@knauf.com

www.usgknauf.com