



## DECLARATION OF PERFORMANCE

No. KAQ\_0400

1. Unique identification code of the product-type: **AQUAPANEL® Exterior Dispersion Plaster – white**  
**EDPW\_87268\_011**
2. Intended use/es: **On external walls, ceilings, columns and partitions**
3. Manufacturer: **Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, D - 58638 Iserlohn**  
**Tel.: +49 2374 5036-0, Fax: +49 2374 5036-300, E-Mail: [aquapanel.info@knauf.com](mailto:aquapanel.info@knauf.com)**
4. Authorised representative: not applicable
5. System/s of AVCP: **System 3**
6. a) Harmonised standard: **EN 15824:2009-07**  
Notified body/ies: **MPA NRW (0432)**
6. b) European Assessment Document / European Technical Assessment / Technical Assessment Body /  
Notified body/ies: not applicable
7. Declared performance/s:

Essential characteristics	Performance	Harmonised tech. specification
Water vapour diffusion coeff. $\mu$	V1	EN 15824:2009-07
Water absorption	W2	EN 15824:2009-07
Adhesion	$\geq 0,3$ MPa	EN 15824:2009-07
Durability (against freeze/thaw)	NPD	EN 15824:2009-07
Thermal conductivity $\lambda$	$\lambda = 0,7$ W/(m·K)	EN 15824:2009-07
Reaction to fire	B-s1, d0	EN 15824:2009-07
Dangerous substances	NPD	EN 15824:2009-07

8. Appropriate Technical Documentation and/or Specific Technical Documentation: not applicable

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr. Thomas Koslowski, General Manager

Iserlohn, 09.06.2016

28.5.2014 L 159/43 Official Journal of the European Union EN

**AQUAPANEL®**

Be certain, choose AQUAPANEL®