

Belgravia (E)

DEMOUNTABLE ACOUSTICAL CEILING

- Robust ceiling with long service life
- Simple, time-saving installation
- Easy service maintenance



Product Datasheet

12/2025

Product description

Demountable acoustic gypsum ceiling in a recessed T-grid system with an edge E design

Recyclable product

Belgravia (E) is made of gypsum, and gypsum as material is recyclable. This means that Belgravia (E) acoustic tiles are recyclable and can be re-used in the production of new gypsum boards and acoustic gypsum tiles.

Product performance

Fire rating

A2-s1, d0

Air quality

Indoor value: 10 days
Particle emission: LOW

Load-bearing capacity

Up to 3 kg pr. tile (at max. 2mm deflection)

Longevity

Belgravia (E) is a longlasting acoustic ceiling with the possibility for reuse within the same long service life. The tiles are repaintable without the loss of acoustics, and can therefore be updated to different styles depending on the trend.

Ambient conditions

Can withstand:
- Constant RH 70% and 25°C
- Periodic RH 90% and 30°C
- Ambient temperatures of up to 50°C.

Product variants

Edge design			
	Edge E, S15 Lay-in tile in recessed S15 T-grid	Edge E, S24 Lay-in tile in recessed S24 T-grid	Edge E, FINELINE Lay-in tile in a C-channelled T-grid

Perforation design					
	Regula Without perforations	Micro Square 3x3 mm c/c 8.33 mm	Globe Circles Ø 6 mm c/c 15 mm	Quadril Square 12x12 mm c/c 30 mm	Tungrit Square 2x12 mm c/c 103/20 mm

Perforation measures	Regula Without perforations	Micro Square 3x3 mm c/c 8.33 mm	Globe Circles Ø 6 mm c/c 15 mm	Quadril Square 12x12 mm c/c 30 mm	Tungrit Square 2x12 mm c/c 103/20 mm
Perforation %	0 %	10.2 %	10.2 %	13 %	21.3%
NRC, @ 200mm, no mineral wool	0.10	0.60	0.65	0.65	0.75
NRC, @ 200mm, 50mm mineral wool	0.10	0.70	0.70	0.75	0.90
ALPHA-W @ 200mm, no mineral wool	0.10	0.65	0.60	0.60	0.80
APLHA-W @ 200mm, 50mm mineral wool	0.10	0.70	0.65	0.70	0.90
Light reflection	82.6 %	72.1 %	72.8 %	75.1%	70.9%
Sizes, mm	Standard	600x600x12.5 625x625x12.5 (only S24)			600x600x12.5
	Other options	300-450 x 600-2400 x 12.5 450-625 x 600-1250 x 12.5			
Tile weight, kg/m²	9.20 - 9.90				
Surface treatment	Front: White acrylic paint, RAL 9003, gloss 5 Back: Acoustic felt backing. Available in other colours on request.				
System components	1) Gypsum ceiling tile, 2) T24/38 or T15/38 main runner, 3) Cross tees, 4) Hangers				
Certificates	1) Environmental product declaration, 2) FDES – life cycle analysis, 3) Danish Indoor Climate Labelling, 4) ISO 16000-9 Emission of VOCs, 5) UL-listed in accordance to R26164				