

## Screw-Jackpoint Self-Drilling MU

Technical Data Sheet 12/2023



## Screw - Jackpoint Self-Drilling MU

Hanger element

### Product Description

Self-drilling screws with countersunk cross-heads for fixing plasterboard to metal substructure from 0,7mm to 2,25 mm thickness.

### Storage

- Direct contact with water should be avoided.
- Packages should be stored in flat, dry and clean areas.

### Referans Standart

EN 14566

### Fields of Application

- Gypsum Board Partition Wall Systems
- Gypsum Board Suspended Ceiling Systems
- Gypsum Board Wall Cladding Systems

### Properties

- Clean and easy installation

# Screw - Jackpoint Self-Drilling MU

Hanger element



## Technical Data

Description	Diameter (mm)	Length (mm)	Weight (kg/box)	Packaging Unit (pcs./pallet)	Material Number
Screw - Jackpoint Self-Drilling MU	3,5	25	1,40 / 22,50	1000 / 16000	141251 / 97991
		35	2 / 17	1000 / 9000	141252 / 97992

### System Performance Values

Performance values as sound insulation, fire resistance etc. may differ acc. to the drywall system to be applied. Please check the performance values of the drywall systems;

[Knauf Technical Website](#)  
[Document Center](#)

### Application

Application should be done acc. to the applicable standards (TS 1475) and acc. to the Knauf Technical Brochures of the respective drywall system.

▶ 444 YAPI - 9274

▶ [www.knauf.com.tr](http://www.knauf.com.tr) / [www.teknik.knauf.com.tr](http://www.teknik.knauf.com.tr)

▶ [teknik@knauf.com](mailto:teknik@knauf.com)

Center: Knauf Moment Beştepe Office, Beştepe Mah. 32.Cadde No:1/212-218 06560 Beştepe-Yenimahalle  
/ ANKARA Tel: 0312 297 0100 Faks: 0312 266 4506