

MineralAktiv Scheibenputz Dry 2.0

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
 Issue date: 1/22/2025 Revision date: 1/22/2025 Supersedes version of: 4/20/2022 Version: 4.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
 Product name : MineralAktiv Scheibenputz Dry 2.0
 Product code : 15566_0010

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
 Main use category : Professional use, Consumer use
 Use of the substance/mixture : Manufacture of mortars

1.2.2. Uses advised against

Restrictions on use : Not to be used for any purpose other than the one the product was designed for

1.3. Details of the supplier of the safety data sheet

Manufacturer

Knauf Gips KG
 Am Bahnhof 7
 DE 97346 Iphofen, Bayern
 Germany
 T +49 9323/31-0, F +49 9323/31-277
sds-info@knauf.com, www.knauf.com

1.4. Emergency telephone number

Country/Area	Organisation/Company	Address	Emergency number	Comment
Europe	Global Incident Response (GIR) Hotline		+1 760 476 3962	Access Code: 336325

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin Irrit. 2 H315
 Eye Dam. 1 H318
 STOT SE 3 H335
 Full text of hazard classes, H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

May cause respiratory irritation. Causes skin irritation. Causes serious eye damage.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS05

GHS07

Signal word (CLP) :

Danger

Contains

calcium hydroxide; Portland cement

MineralAktiv Scheibenputz Dry 2.0

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazard statements (CLP)	: H315 - Causes skin irritation. H318 - Causes serious eye damage. H335 - May cause respiratory irritation.
Precautionary statements (CLP)	: P102 - Keep out of reach of children. P261 - Avoid breathing dust. P280 - Wear protective gloves, protective clothing, eye protection, face protection. P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P310 - Immediately call a POISON CENTER or doctor. P501 - Dispose of contents and container to Recycle or dispose of in compliance with current legislation.

2.3. Other hazards

Contains no PBT and/or vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	calcium hydroxide (1305-62-0), Portland cement (65997-15-1), quartz, conc respirable crystalline silica<1% (14808-60-7)
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	calcium hydroxide (1305-62-0), Portland cement (65997-15-1), quartz, conc respirable crystalline silica<1% (14808-60-7)

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
quartz, conc respirable crystalline silica<1% substance with a Community workplace exposure limit	CAS-No.: 14808-60-7 EC-No.: 238-878-4	< 20	Not classified
calcium hydroxide substance with a Community workplace exposure limit	CAS-No.: 1305-62-0 EC-No.: 215-137-3 REACH-no: 01-2119475151-45	< 15	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335
Portland cement	CAS-No.: 65997-15-1 EC-No.: 266-043-4	< 15	Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335

Comments : Low in chromate according to EU-Regulation 1907/2006 (REACH).
The contained Portland cement is white cement.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Take off contaminated clothing. Wash contaminated clothing before reuse. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If you feel unwell, seek medical advice. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Rinse and then wash skin thoroughly with water and soap. Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.

MineralAktiv Scheibenputz Dry 2.0

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth thoroughly with water. Immediately give plenty of water. Get medical advice/attention. Call a poison center or a doctor if you feel unwell.
First-aid measures for first aider	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: None under normal conditions.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam.
Unsuitable extinguishing media	: Strong water jet.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Not combustible.
Explosion hazard	: No direct explosion hazard.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Advice for firefighters

Firefighting instructions	: Fight fire from safe distance and protected location. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures	: Wear personal protective equipment. Keep public away from danger area. Evacuate personnel to a safe area. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material damage.
------------------	---

6.1.1. For non-emergency personnel

Protective equipment	: Wear recommended personal protective equipment.
Emergency procedures	: Ventilate spillage area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Evacuate unnecessary personnel.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Using a clean shovel, put the material in a dry container and cover without compressing it.
Methods for cleaning up	: Mechanically recover the product. Avoid creating or spreading dust.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

MineralAktiv Scheibenputz Dry 2.0

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed	: Not expected to present a significant hazard under anticipated conditions of normal use.
Precautions for safe handling	: Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes. Wear personal protective equipment.
Hygiene measures	: Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures	: Keep in a cool, well-ventilated place away from heat.
Storage conditions	: Store locked up. Store in a well-ventilated place. Keep container tightly closed.
Packaging materials	: Store always product in container of same material as original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

calcium hydroxide (1305-62-0)

EU - Indicative Occupational Exposure Limit (IOEL)

Local name	Calcium dihydroxide
IOEL TWA	1 mg/m ³ (Respirable fraction)
IOEL STEL	4 mg/m ³ (Respirable fraction)
Regulatory reference	COMMISSION DIRECTIVE (EU) 2017/164

quartz, conc respirable crystalline silica<1% (14808-60-7)

EU - Indicative Occupational Exposure Limit (IOEL)

Local name	Silica crystalline (Quartz)
IOEL TWA	0.05 mg/m ³ (respirable dust)
Remark	(Year of adoption 2003)
Regulatory reference	SCOEL Recommendations

EU - Binding Occupational Exposure Limit (BOEL)

Local name	Respirable crystalline silica dust
BOEL TWA	0.1 mg/m ³ (Respirable fraction)
Regulatory reference	DIRECTIVE (EU) 2019/130 (amending Directive 2004/37/EC)

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

MineralAktiv Scheibenputz Dry 2.0

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

8.2.2. Personal protection equipment

Personal protective equipment:

Wear recommended personal protective equipment.

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

Eye protection

Type	Field of application	Characteristics	Standard
Safety glasses			EN 166

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Protective gloves

Hand protection

Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Chemically resistant protective gloves	Nitrile rubber (NBR)	6 (> 480 minutes)			EN ISO 374

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

Respiratory protection

Device	Filter type	Condition	Standard
Dust mask	Type P2	Dust protection	EN 149

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Consumer exposure controls:

Ensure adequate ventilation, especially in confined areas. Avoid contact with skin and eyes. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Take off contaminated clothing and wash it before reuse. Do not eat, drink or smoke when using this product.

MineralAktiv Scheibenputz Dry 2.0

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid
Colour	: White. Yellow. brown. Green. Blue. dark blue. Black. Grey. red.
Appearance	: Powders.
Odour	: earthy.
Odour threshold	: Not available
Melting point	: Not available
Freezing point	: Not available
Boiling point	: Not available
Flammability	: Non flammable.
Explosive properties	: Product is not explosive.
Lower explosion limit	: Not applicable
Upper explosion limit	: Not applicable
Flash point	: Not applicable
Auto-ignition temperature	: Not self-igniting
Decomposition temperature	: 580 °C
pH	: 10 – 12
pH solution	: 10 % Suspension
Viscosity, kinematic	: Not applicable
Solubility	: Not available
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: Not available
Relative vapour density at 20°C	: Not applicable
Particle size	: Not available

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

Bulk density : 600 – 1500 kg/m³

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

MineralAktiv Scheibenputz Dry 2.0

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (dermal) : Not classified (Based on available data, the classification criteria are not met)
Acute toxicity (inhalation) : Not classified (Based on available data, the classification criteria are not met)

calcium hydroxide (1305-62-0)	
LD50 oral rat	> 2000 mg/kg bodyweight (OECD 425: Acute Oral Toxicity: Up-and-Down Procedure, Rat, Female, Experimental value, Oral, 14 day(s))
LD50 dermal rabbit	> 2500 mg/kg bodyweight (OECD 402: Acute Dermal Toxicity, 24 h, Rabbit, Male / female, Experimental value, Dermal, 14 day(s))
LC50 Inhalation - Rat	> 6.04 mg/l (OECD 436: Acute inhalation toxicity-acute toxic class method, 4 h, Rat, Male / female, Experimental value, Inhalation (dust), 15 day(s))
Skin corrosion/irritation	: Causes skin irritation. pH: 10 – 12

calcium hydroxide (1305-62-0)	
pH	12.4 (0.18 %, 20 °C, EU Method A.6: Water solubility)

Portland cement (65997-15-1)	
pH	11 – 13.5 (20 °C)

quartz, conc respirable crystalline silica<1% (14808-60-7)	
pH	6 – 7

Serious eye damage/irritation : Causes serious eye damage.
pH: 10 – 12

calcium hydroxide (1305-62-0)	
pH	12.4 (0.18 %, 20 °C, EU Method A.6: Water solubility)

Portland cement (65997-15-1)	
pH	11 – 13.5 (20 °C)

quartz, conc respirable crystalline silica<1% (14808-60-7)	
pH	6 – 7

Respiratory or skin sensitisation : Not classified (Based on available data, the classification criteria are not met)
Germ cell mutagenicity : Not classified (Based on available data, the classification criteria are not met)
Carcinogenicity : Not classified (Based on available data, the classification criteria are not met)

quartz, conc respirable crystalline silica<1% (14808-60-7)	
IARC group	1 - Carcinogenic to humans

Reproductive toxicity : Not classified (Based on available data, the classification criteria are not met)
STOT-single exposure : May cause respiratory irritation.

calcium hydroxide (1305-62-0)	
STOT-single exposure	May cause respiratory irritation.

Portland cement (65997-15-1)	
STOT-single exposure	May cause respiratory irritation.

STOT-repeated exposure : Not classified (Based on available data, the classification criteria are not met)
Aspiration hazard : Not classified (Based on available data, the classification criteria are not met)

calcium hydroxide (1305-62-0)	
Viscosity, kinematic	Not applicable (solid)

MineralAktiv Scheibenputz Dry 2.0

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Portland cement (65997-15-1)

Viscosity, kinematic	Not applicable (solid)
----------------------	------------------------

quartz, conc respirable crystalline silica<1% (14808-60-7)

Viscosity, kinematic	Not applicable (solid)
----------------------	------------------------

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Adverse health effects caused by endocrine disrupting properties

: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

11.2.2. Other information

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term (acute) : Not classified (Based on available data, the classification criteria are not met)

Hazardous to the aquatic environment, long-term (chronic) : Not classified (Based on available data, the classification criteria are not met)

calcium hydroxide (1305-62-0)

LC50 - Fish [1]	50.6 mg/l (OECD 203: Fish, Acute Toxicity Test, 96 h, Oncorhynchus mykiss, Static system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	49.1 mg/l (OECD 202: Daphnia sp. Acute Immobilisation Test, 48 h, Daphnia magna, Static system, Fresh water, Experimental value, Estimated value)
ErC50 algae	184.57 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Nominal concentration)

Portland cement (65997-15-1)

LC50 - Fish [1]	> 1000 mg/l (96 h, Pisces)
-----------------	----------------------------

12.2. Persistence and degradability

MineralAktiv Scheibenputz Dry 2.0

Persistence and degradability	Rapidly degradable
-------------------------------	--------------------

calcium hydroxide (1305-62-0)

Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

Portland cement (65997-15-1)

Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)
BOD (% of ThOD)	Not applicable

MineralAktiv Scheibenputz Dry 2.0

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

quartz, conc respirable crystalline silica<1% (14808-60-7)

Persistence and degradability	Biodegradability: not applicable, No (test)data on mobility of the substance available.
Chemical oxygen demand (COD)	Not applicable
ThOD	Not applicable

12.3. Bioaccumulative potential

calcium hydroxide (1305-62-0)

Bioaccumulative potential	Not bioaccumulative.
---------------------------	----------------------

Portland cement (65997-15-1)

Bioaccumulative potential	No bioaccumulation data available.
---------------------------	------------------------------------

quartz, conc respirable crystalline silica<1% (14808-60-7)

Bioaccumulative potential	No bioaccumulation data available.
---------------------------	------------------------------------

12.4. Mobility in soil

calcium hydroxide (1305-62-0)

Surface tension	72 mN/m (20 °C, 0.1 %, OECD 115: Surface Tension of Aqueous Solutions)
Ecology - soil	Adsorbs into the soil.

Portland cement (65997-15-1)

Surface tension	No data available in the literature
Ecology - soil	No (test)data on mobility of the substance available.

quartz, conc respirable crystalline silica<1% (14808-60-7)

Surface tension	No data available in the literature
Ecology - soil	Low potential for mobility in soil.

12.5. Results of PBT and vPvB assessment

Component

Substance(s) not meeting the PBT criteria of REACH regulation, in accordance with Annex XIII	calcium hydroxide (1305-62-0), Portland cement (65997-15-1), quartz, conc respirable crystalline silica<1% (14808-60-7)
Substance(s) not meeting the vPvB criteria of REACH regulation, in accordance with Annex XIII	calcium hydroxide (1305-62-0), Portland cement (65997-15-1), quartz, conc respirable crystalline silica<1% (14808-60-7)

12.6. Endocrine disrupting properties

Adverse effects on the environment caused by endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %.

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional waste regulation	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Sewage disposal recommendations	: Disposal must be done according to official regulations.

MineralAktiv Scheibenputz Dry 2.0

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Product/Packaging disposal recommendations	: Comply with applicable regulations for solid waste disposal. Disposal must be done according to official regulations.
Additional information	: Do not re-use empty containers. The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process. Waste Codes are only suggestions.
European List of Waste (LoW, EC 2000/532)	: 17 01 06* - mixtures of, or separate fractions of concrete, bricks, tiles and ceramics containing dangerous substances 17 09 03* - other construction and demolition wastes (including mixed wastes) containing dangerous substances
HP Code	: HP5 - "Specific Target Organ Toxicity (STOT)/Aspiration Toxicity:" waste which can cause specific target organ toxicity either from a single or repeated exposure, or which cause acute toxic effects following aspiration. HP4 - "Irritant – skin irritation and eye damage:" waste which on application can cause skin irritation or damage to the eye.

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.2. UN proper shipping name				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.4. Packing group				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards				
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

Inland waterway transport

Not applicable

Rail transport

Not applicable

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

MineralAktiv Scheibenputz Dry 2.0

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Other information, restriction and prohibition regulations : Directive 2012/18/EU (SEVESO III): Not applicable.

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)

Reference code	Applicable on
47.	Portland cement

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

Council Regulation (EC) for the control of dual-use items

Contains no substance subject to the COUNCIL REGULATION (EC) for the control of dual-use items

Explosives Precursors Regulation (2019/1148)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out

SECTION 16: Other information

Indication of changes

Section	Changed item	Comments
	Revision date	Modified
	Issue date	Modified
	Adverse health effects caused by endocrine disrupting properties	Added
1.2	Use of the substance/mixture	Added
1.2	Restrictions on use	Added
1.2	Main use category	Added
1.2	Intended for general public	Added

MineralAktiv Scheibenputz Dry 2.0

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes		
Section	Changed item	Comments
2.1	Adverse physicochemical, human health and environmental effects	Added
2.1	Intended for general public	Added
2.2	Precautionary statements (CLP)	Modified
4.1	First-aid measures for first aider	Added
4.1	First-aid measures general	Added
4.1	First-aid measures after skin contact	Added
4.1	First-aid measures after inhalation	Added
4.1	First-aid measures after ingestion	Added
4.1	First-aid measures after eye contact	Added
4.2	Symptoms/effects after skin contact	Added
4.2	Symptoms/effects after inhalation	Added
4.2	Symptoms/effects after ingestion	Added
4.2	Symptoms/effects after eye contact	Added
4.3	Other medical advice or treatment	Added
5.1	Unsuitable extinguishing media	Added
5.1	Suitable extinguishing media	Added
5.2	Hazardous decomposition products in case of fire	Added
5.2	Fire hazard	Added
5.2	Explosion hazard	Added
5.3	Protection during firefighting	Added
5.3	Firefighting instructions	Added
6.1	Protective equipment	Added
6.1	Emergency procedures	Added
6.1	Protective equipment	Added
6.1	Emergency procedures	Added
6.1	General measures	Added
6.2	Environmental precautions	Added
6.3	For containment	Added
6.3	Methods for cleaning up	Added
6.3	Other information	Added
6.4	Reference to other sections (8, 13)	Added
7.1	Additional hazards when processed	Added
7.1	Precautions for safe handling	Added
7.1	Hygiene measures	Added
7.2	Technical measures	Added
7.2	Storage conditions	Added
7.2	Packaging materials	Added

MineralAktiv Scheibenputz Dry 2.0

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Indication of changes		
Section	Changed item	Comments
8.2	Environmental exposure controls	Added
8.2	Consumer exposure controls	Added
8.2	Respiratory protection	Added
8.2	Personal protective equipment	Added
8.2	Hand protection	Added
8.2	Eye protection	Added
8.2	Appropriate engineering controls	Added
8.2	Skin and body protection	Added
9	Flammability (solid, gas)	Added
9	Colour	Modified
10.1	Reactivity	Added
10.2	Chemical stability	Added
10.3	Possibility of hazardous reactions	Added
10.4	Conditions to avoid	Added
10.6	Hazardous decomposition products	Added
13.1	HP Code	Added
13.1	European List of Waste (LoW, EC 2000/532)	Added
13.1	Waste treatment methods	Added
13.1	Product/Packaging disposal recommendations	Added
13.1	Sewage disposal recommendations	Added
13.1	Additional information	Added
13.1	Regional waste regulation	Added
15.1	Other information, restriction and prohibition regulations	Added
15.1	REACH Annex XVII	Added
15.2	Chemical safety assessment	Added
16	Training advice	Added
16	Abbreviations and acronyms	Added
16	Other information	Added

Abbreviations and acronyms:	
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
COD	Chemical oxygen demand (COD)

MineralAktiv Scheibenputz Dry 2.0

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms:	
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
EN	European Standard
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
REACH	Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
TRGS	Technical Rules for Hazardous Substances
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
VOC	Volatile Organic Compounds
CAS-No.	Chemical Abstract Service number
WGK	Water Hazard Class
vPvB	Very Persistent and Very Bioaccumulative
IOELV	Indicative Occupational Exposure Limit Value
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008

Training advice : Normal use of this product shall imply use in accordance with the instructions on the packaging. Carefully comply with the instructions for use. Comply with instructions for use (refer to technical sheet). Comply with the safety procedures. Observe the label precautions. Ensure all national/local regulations are observed.

Full text of H- and EUH-statements:	
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
H315	Causes skin irritation.
H318	Causes serious eye damage.
H335	May cause respiratory irritation.
Skin Irrit. 2	Skin corrosion/irritation, Category 2

MineralAktiv Scheibenputz Dry 2.0

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:

STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation
-----------	--

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Skin Irrit. 2	H315	Calculation method
Eye Dam. 1	H318	Calculation method
STOT SE 3	H335	Calculation method

KNAUF SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.