



Knauf Nonius Stirrup

Bottom part of the nonius hanger system which is attached to the CD channels.
Designed exclusively to be used with Knauf D112 ceiling system.

Knauf Nonius Stirrup

Properties

Bottom part of the nonius hanger system which is attached to the CD channels.

Technical Data

Dimensions	Packing Details	
Width (mm)	Pieces Per Pack	Weight Per Pack (Kg approx.)
60	100	11

Load bearing capacity class = 40 kg.



Please contact our sales department for inquiries about storage and packing.

Note:

Knauf Head Office

- ▶ Phone: +971 4 337 7170
- ▶ Fax: +971 4 334 9659
- ▶ P.O.Box: 112871, Dubai
- ▶ info.uae@knauf.com

Knauf Manufacturing Plant

P.O.Box 50006
 Ras Al Khaimah, U.A.E.
 Tel: +971 7 268 9837
 Fax: +971 7 221 5301



Disclaimer:

The information provided in this leaflet is only intended to give guidance in selecting and using Knauf products. While we make every effort to ensure its accuracy, neither Knauf LLC and its branches nor any of its employees or affiliates warrant or assume any legal liability or responsibility for the completeness or usefulness of any failure in installation or constructing any structure installation or building or caused by using this leaflet. Readers are advised to independently verify this information prior to rely on it. In particular, readers must obtain appropriate independent advice on the use in specific structures, installations or buildings to ensure compliance with all regulations, including health and safety regulations. Knauf reserves the right to amend technical specification.

The constructional and structural properties, and characteristic building physics Knauf system can solely be ensured with the exclusive use Knauf system components, or other product expressly recommended by Knauf.