

KNAUF

Knauf Betokontakt

Knauf Betokontakt is a polymer based product designed to provide a key to backgrounds which are smooth or have limited suction, such as reinforced concrete that requires pre-treatment.

Product-Data-Sheet



Areas of Application

Plasterboard walls and ceilings

Compliance Standards

This product does not have a harmonised standard to allow for CE marking and or designated standard to allow for UKCA marking.

Key Benefits

- Use with Knauf Moisture Panel or Knauf Performance Plus before applying gypsum plaster skim
- EC1 Plus Emission rated for very low emissions

Build on us.

Creation Date: 26/06/2024
Revision Reference: 002
Revision Date: 15/01/2025

Performance Data

Reaction to Fire (R2F)	Thermal Conductivity (λ)	Dangerous Substances (DS)	Adhesion (MPa)
A2-s1,d0	NPD	NPD	>0.3

Technical Information

Colour	Weight (kg)	Approximate Coverage (m ²)	Material Number
Pink	20	89.0* per tub	545454

* depending on substrate

Sustainability

Substances of very high Concern (SVHC)

At the time of publication, under REACH UK and REACH EU regulations this product contains no SVHC. For more information please consult the Safety Data Sheet.

Volatile Organic Compound Content (VOC)

< 0.1% (<1 g/L).

Storage and Handling

Store and apply between 5°C to 30°C. Close the opened tub after use to keep airtight. Do not expose to direct sunlight or heat.

Packaging

In a recycled plastic tub, recyclable after use.

Shelf Life

18 months.

Disposal/Repair

Disposal should be in accordance with local authority requirements. Containers should be cleaned before recycling to minimise contamination.

Health & Safety

Goggles with side shields are recommended in case of splashing. For more information please consult the safety data sheet.

Application

Can be applied with a brush, roller, or by spraying. Minimum of 12 hours drying time at 20°C 65% relative humidity (RH). When being applied to reinforced concrete structures, before bonding compound is applied please ensure the surface is cleaned with a cleaning agent and brush to remove any additional oils used in the construction process.

Ensure the Betokontakt has completely dried before applying a subsequent layer of surface finish plaster.

Product Accreditations:



Knauf UK GmbH Company Accreditations:



The information given in this publication is believed to be current and accurate as at the date of publication, but no warranty, express or implied is given. Updates will not be automatically issued © Copyright Knauf 2024

Customer Service

UK Tel: 0800 521 050
Eire Tel: 01 4620739
Email: cservice@knauf.com

Technical Service

Tel: 0800 521050 (option 2)
Email: technical-uk@knauf.com
(excluding public holidays)

UK Address

Knauf
Kemsley Fields Business Park
Sittingbourne
Kent ME9 8SR

Ireland Address

Knauf
87 Broomhill Road
Tallaght
Dublin 24
D24 WR85

Creation Date: 26/06/2024
Revision Reference: 002
Revision Date: 15/01/2025