

Knauf – One of worldwide market leaders in providing customers with light-weight material Solution

“Knauf Group, a German-based global company operating across 90 countries worldwide, acquired Sheetrock as part of its acquisition of USG in 2018. The synergies from this acquisition increases Knauf’s capability to provide products and systems for light-weight building material that are environment-friendly, energy-efficient, and fairly-priced to help customers work and build better.”

Knauf – One of leading German brands for builders to Build a Better Living Space.



KNAUF VIETNAM CO., LTD.

HO CHI MINH OFFICE: 7th Floor, Harbour View Tower, 35 Nguyen Hue Street, Ben Nghe Ward, District 1, Ho Chi Minh City, Vietnam	HO CHI MINH Plant: Lot B3a, Hiep Phuoc Industrial Zone, Hiep Phuoc Commune, Nha Be Ward, Ho Chi Minh City, Vietnam	HANOI OFFICE: 8th Floor, Capital Place Building, 29 Lieu Giai Street, Ba Dinh District, Ha Noi, Vietnam	HAI PHONG Plant: Land Plot CN4.4A, Dinh Vu IP, Dinh Vu - Cat Hai Economic Zone, Dong Hai 2 Ward, Hai An District, Hai Phong City, Vietnam
Tel: +84 28 3915 1400 Fax: +84 28 3915 1405	Tel: +84 28 3781 8439 Fax: +84 28 3781 8440	Tel: +84 24 3791 8412 Fax: +84 24 3791 8413	Tel: +84 225 883 0660 Fax: +84 225 883 0686

knauf.com/vi-vn | info-vn@knauf.com | <https://www.facebook.com/knaufvietnam>

Remarks: Information provided is for reference purpose only. Products, specifications and requirements may vary according to geographical locations and applications. As each project is unique, please contact your nearest Knauf representative for further product, solution and technical supports.

This document is owned by Knauf Vietnam Co., Ltd. Last update: 06/2025

knauf

EASYJOINT90
Compound

Build on us.

knauf

EASYJOINT90

Compound

Compound EASYJOINT90

EASYJOINT90 is used to treat and finish Plasterboard joints and screw points. It has crack resistance, high adhesion, smooth texture, and is easy to apply and sand.

The main component is gypsum powder, used for finishing seamless plasterboard joints, angles and fastener heads in partition, ceilings and wall linings. With a quick and stable setting time of 90 minutes, EASYJOINT90 helps significantly reduce construction time, control project progress, and ensure quality.

Advantages

- High crack resistance joints when used with paper tape
- High adhesive
- Stable setting time
- Easy to sand, allowing a smooth finish to be easily achieved
- Material savings



Setting time:	90 minutes (*)
Mixing ratio:	1 part of water & 2 parts of powder (**)
Coverage:	65m ² / bag 20kg (***)
Weight:	20kg/ bag
Shelf life:	6 months (from manufacturing date)

(*) Depend on environmental conditions

(**) By weight







(***) Depend on 3 layers application



PACKAGING



INSTRUCTION FOR INSTALLATION

Plasterboard Tapered Edge	Plasterboard Square Edge
	
Step 1: Apply a 150mm wide layer combined with Knauf joint tape	Step 1: Apply a 300mm wide layer combined with Knauf joint tape
	
Step 2: Apply the second layer with a width of 200mm	Step 2: Apply the second layer with a width of 400mm
	
Step 3: Apply the third layer to finish with a width of 300mm	Step 3: Apply the third layer to finish with a width of 500mm

NOTES

- EASYJOINT90 should not be mixed with other jointing compound products.
- EASYJOINT90 should only be used in interior application.
- All types of plasterboard require light sanding before painting.
- EASYJOINT90 should be manipulated and applied based on Knauf Technical Manual.