








AMF ECOMIN Trento

- AMF ECOMIN Trento is a cost effective ceiling solution that features a uniform textured finish. It provides good acoustic absorption for areas that need acoustic comfort
- Ideal for retail, offices and meeting rooms, installations rooms or production areas



AMF ECOMIN TRENTO

Edge details Additional edge details on request	Board 														
Thickness (mm)	13														
Dimensions (mm) Additional sizes on request	600 x 600														
System	Exposed demountable - System C														
Weight	3.1 kg / m ²														
Colour	White														
Sound absorption	EN ISO 354 $\alpha_w = 0.55$ as per EN ISO 11654 - Class D <table border="1" data-bbox="459 884 1452 963"> <thead> <tr> <th>Frequency f (Hz)</th> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> </tr> </thead> <tbody> <tr> <td>α_p</td> <td>0.55</td> <td>0.55</td> <td>0.50</td> <td>0.55</td> <td>0.60</td> <td>0.60</td> </tr> </tbody> </table> NRC = 0.55 as per ASTM C 423	Frequency f (Hz)	125	250	500	1000	2000	4000	α_p	0.55	0.55	0.50	0.55	0.60	0.60
Frequency f (Hz)	125	250	500	1000	2000	4000									
α_p	0.55	0.55	0.50	0.55	0.60	0.60									
Fire reaction	Euroclass A2-s1, d0 as per EN 13501-1 RUS KM1 (G1, V1, D1, T1) as per 123-FZ														
Light reflectance	83%														
Thermal conductivity	$\lambda = 0.060$ W/mk as per EN 12667														
Humidity resistance	70% RH														
Indoor air quality	  A+ E1														
Cleanability	 														
Sustainability	   46%														

Products may vary from country to country. Please contact your local sales representative. For further information and legal notice, please visit our website.