



PRODUCT DESCRIPTION

EASYJOINT90 is a high quality gypsum-based compound used for nishing seamless plasterboard joints, angles and fastener heads in partition, ceilings and wall linings.

Product Specification

Setting time	90 minutes(*)
Mixing ratio:	1 part of water & 2 parts of powder (**)
Coverage	65m ² / bag 20kg (***).
Weight	20kg/ bag.
Shelf life	6 months (from manufacturing date).

(*) Depends on weather conditions.

(**) by weight

(***) depend on 3 layers application, square or tapered edge.

ADVANTAGES

- Easy to mix and apply, require less effort.
- Easy to sand, allowing a smooth nish to be easily achieved.
- High crack resistance joints when used with paper tape.
- Provide high strength joints beneath thin coat skimming.
- Material savings.
- Stable setting time.
- High adhesive.

TECHNICAL INFORMATION

Standard:

- TCVN 12693:2020

SUBMITTAL SHEET

04/2024

Specifications:

Items	Unit	Results	Specifications	Test Method
Setting time	Minutes	80	$60 \leq t \leq 180$ (Normal setting)	TCVN 12693:2020
Cracking	-	No crack	No crack	
Adhesion strength	MPa	0,30	$\geq 0,25$	
Particle size distribution - 200 μm sieves - 315 μm sieves	%	0 0	≤ 1 0	

Note: The results of experimental criteria meet the technical requirements of the joining compound according to TCVN 12693: 2020

APPLICATION

EASYJOINT90 is used for bonding joints and finishing ceiling systems, partitions, because of its ability to help adhere well between the joint treatment tape and the surface of plasterboard. With drying time, fast and stable simmering in 90 minutes, EASYJOINT90 powder helps shorten construction time significantly, control progress and ensure quality.

INSTRUCTION FOR
INSTALLATION

Plasterboard Tapered Edge.

Step 1: Apply EASYJOINT90 to the edge joint with paper tape bedded into, width 150mm.

Step 2: Once the rst coat has completely set, a second coat must be applied. Apply EASYJOINT90 to the edge joint with the width 200mm.

Step 3: Once the second coat has completely set, the joint must be lightly scraped -at. Apply EASYJOINT90 to the edge joint with the width 300mm.

Plasterboard Square Edge.

Step 1: Apply EASYJOINT90 to the edge joint with paper tape bedded into, width 300mm.

Step 2: Once the rst coat has completely set, a second coat must be applied. Apply EASYJOINT90 to the edge joint with the width 400mm.

Step 3: Once the second coat has completely set, the joint must be lightly scraped -at. Apply EASYJOINT90 to the edge joint with the width 500mm.

STORAGE AND
TRANSPORTATION

Stored and transported in dry, non-wet conditions (not under the impact of rain, seepage and poor ventilation in prolonged high humidity condition).

LIMITATION

For interior use only and must be stored indoor, in a dry place during construction and storage. Wall, floor, and other enclosed areas must be dry before closing and finishing the interior.