

Easy Board®

Light-weight gypsum board with smooth surface

Product Description

Smooth, flexible and light-weight gypsum board. Front face covered with ivory, back face covered with grey paper.

Storage

Boards should be stored on pallets in a dry environment. If the boards are stored inside, max. 6 pallets on each other; outside max. 5 pallets on each other. Gypsum boards should be stored so as to prevent damage to the front faces of each boards during packaging. If the boards are stored outside, they must be covered with nylon and etc.

Standard

TS EN 520 + A1 - Type A



Fields of Application

- Suspended ceilings

Properties

- Easy application
- Time saving
- High Surface Quality

Technical Data

Description	Unit	12,5 mm	Standard
Board type	-	Type A	TS EN 520+A1
Reaction to fire	class	A2-s1,d0	TS EN 520+A1
Weight	kg/m ²	appx. 6,6	-
Long edges	-	Tapered edges 	-
Front edges	-	Cut edges 	-
Width dimensional tolerance	mm	+0 / -4	TS EN 520+A1
Length dimensional tolerance	mm	+0 / -5	TS EN 520+A1
Thickness dimensional tolerance	mm	+0,5 / -0,5	TS EN 520+A1
Angularity dimensional tolerance (for 1 m board width)	mm	≤ 2,5	TS EN 520+A1
Thermal conductivity λ	W/ (m·K)	0,25	EN 12524
Water vapour resistance factor (dry)	μ	10	EN 12524
Water vapour resistance factor (wet)	μ	4	EN 12524
Flexural breaking load longitudinal direction	N	≥ 550	TS EN 520+A1
Flexural breaking load transverse direction	N	≥ 210	TS EN 520+A1

Product Range

Description	Width (mm)	Length (mm)	Weight (kg/m ²)	Packaging Unit (pcs./pallet)	Material Number
Easy Board® 12,5 mm	1200	2000	approx. 6,6	60	695893
		2500			695891

System Performance Values

There are no performance values given for applications with Easy Board®. In areas with performance requirements, it is advised to contact Knauf Technical Department for different gypsum board systems.

[Knauf Technical Website](#)
[Document Center](#)

Application

Application should be done acc. to the applicable standards (TS 1475) and acc. to the Knauf Technical Brochures of the respective drywall system.

▶ 444 YAPI - 9274

▶ www.knauf.com.tr / www.teknik.knauf.com.tr

▶ teknik@knauf.com

Center: Knauf Moment Beştepe Office, Beştepe Mah. 32.Cadde No:1/212-218 06560 Beştepe-Yenimahalle
/ ANKARA Tel: 0312 297 0100 Faks: 0312 266 4506