



Knauf FILLERPRO

10.2023

KNAUF FILLERPRO 24H

Premium jointing compound for plasterboard

- Smooth, lump-free consistency
- Fine white colour finish
- Easy application
- Strong bonding
- High yield
- 24 hours drying time
- 6 months storage duration



www.knauf.dz

Oran Head Office
CW N °64, 31063 Benfreha, Gdyl, Oran, Algeria
Postal Box N °02, 31240 Boufatis, Oran, Algeria
Tel : +213(0)41 76 34 70/ 71
Fax : +213(0)41 76 34 75/78

Sales Department Algiers
Industrial Aera, EL ACHOUR °23
16034 Algiers, Algeria
Tel : +213 (0° 21 23 93 14

Setif Regional Office
ALN Street, Business Center Park Mall
19000, Setif, Algeria



Technical specifications and implementation*

Scope

Knauf FILLERPRO 24H is a slow drying jointing compound, used to make joints between plasterboard type KNAUF BA (thin edge) or HRAK (semi-rounded thin edge). It must be applied together with a joint tape.

Support

Plasterboard must be fixed and stable on its support (profiles or wall).

Board joints must be clean and dry, free of dust or other impurities that could interact with the product.

Composition

Knauf FILLERPRO 24H is a very fine white powder formulated with calcium carbonate and additives.

Application

Use a clean container, free of any impurities or previous mixing.

Pour clean and fresh water, then powder according to the desired quantity of paste while respecting the mixing rate.

Let the compound absorb the water for 2 to 3 minutes then mix regularly and energetically, (preferable mechanically) until

you get a homogeneous paste, with a good consistency free of lumps.

Apply a first layer on the joint and then add the joint tape.

Use the spatula to remove the excess paste. The layer should not be more than 1 mm, otherwise the joint will dry very slowly.

After drying the first layer, add a second layer and let it dry. If necessary, apply a third layer, once the previous ones dry, it will be necessary to avoid overloading.

It is important to respect the drying time between two layers to avoid the risk of cracking.

Once dry, sand the joint without forcing.

Immediately clean work tools with water.

The paste remains usable for 24 hours, with the same consistency, when kept in a closed container.

Work tools must be clean.

Standards and Certifications

Manufactured to EN 13963 – Composite coating – Type 3A standard

Storage

Store in a dry and closed place, away from moisture, the product must be isolated from the ground (Eg: On a pallet, plastic sheet or other means).

The product remains usable up to 6 months, under the right storage conditions.

Remark

Once dried, the remaining paste in the container should not be used.

Dirty tools and containers cause premature drying and can create adhesion defects or other issues.

It is not recommended to use a paste that has been prepared for more than 24 hours.

Technical data

Water/Powder ratio: 10 l / 20 Kg

Drying time : 24H

*It is recommended to contact our technical department

Dust, in general, is irritating to the respiratory apparatus and can cause cough and other disorders. | IN CASE OF EYE CONTACT: Rinse carefully with water for several minutes, remove contact lenses if the victim is wearing them and they can be easily removed and continue rinsing. | Seek medical attention immediately. | Dispose of contents/container in accordance with local/regional/national/international regulations.



This sheet is intended to inform our customers. It cancels all the previous ones. The data correspond to the most recent state of our knowledge, but in no way can we be held liable for misuse. We recommend that you contact our technical services for more information.