

KNAUF

CE

**KNAUF CYPRUS LTD
CHRISTOY ZEIPEKKI 1
4504 VASA KELLAKIOY**

06

**SK 01:12/03/2014
MZP PROJECTION PLASTER**

CYS EN 998-1:2016

**General purpose rendering / plastering mortar (GP) for
external and internal application – CS II**

Reaction to fire	A1
Adhesion	0.08N/mm ² FP:A
Compressive strength	CSII
Water absorption	W0
Water vapour diffusion coeff	μ25
Thermal conductivity	0,83 W/m·K for P = 50% , 0,93 W/m·K for P = 90% (tab. mean value)
Durability (against freeze / thaw)	Evaluation based on provisions valid in the intended place of use of the mortar

KNAUF

CE

KNAUF CYPRUS LTD
ΧΡΙΣΤΟΥ ΖΕΙΠΕΚΚΗ 1
4504 ΒΑΣΑ ΚΕΛΛΑΚΙΟΥ

06

SK 01:12/03/2014
MZR PROJECTION PLASTER

CYS EN 998-1:2016

**Κονιάμα τοιχοποιίας γενικής χρήσης για εσωτερικές
και εξωτερικές εφαρμογές CSII**

Κλάση πυραντίστασης

A1

Πρόσφυση

0.08N/mm² - FP:A

Αντοχή σε θλίψη

CSII

Υδατοαπορρόφηση

W0

Διαπερατότητα υδρατμών

μ25

Θερμική αγωγιμότητα

0,83 W/m·K for P = 50%, 0,93 W/m·K for P = 90% (τιμή από πίνακες)

Ανθεκτικότητα

Αξιολόγηση που βασίζεται στην διάταξη που ισχύουν στον προοριζόμενο τόπο χρήσης του επιχρίσματος