


Acoustical wall panel



Content

Demountable acoustic gypsum wall for acoustic regulation.
Laminated surface with possibility for individual surface designs.
100% recyclable product.

Products and materials

Tangent_450 x < 1200/2400 > x 9.5_B

Material: Perforated plasterboard
Board Type: Gypsum panel
Dimensions: 450 x <1200/2400> x 9.5mm
Weight: 4.0 and 8.0 kg/panel
Edge: B, mitred and glued long edges
Perforation: Obround 4x14mm holes, c/c 10/20mm.
Perforation percent: 23.9 – 24.5%
Surface: Laminated foil (PVC-free), pH resistant 2.5 - 13.0
(Individual print design on request)
Colour: Ultra white NCS S0300-N, (RAL 9016); gloss 10
Light reflection: 74.1% in accordance with DIN 5036
Fire rating: B-s1,d0 in accordance with EN 13501-1
Indoor climate: Degasification 10 days
Particle emission: Low
Air purification: Cleaneo technology

Acoustics

55mm installation depth with 33mm mineral wool

125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	α_w	NRC
0.25	0.65	0.90	0.90	0.85	0.80	0.90	0.85

Accessories

ADIT comes as a kit with 2xpanels and all the accessories needed.

Installation

- In accordance with included installation guide that comes along with the kit.