



# Knauf Ceiling U Channel

## Profile

### Product Description

Galvanized lightweight steel section for use in gypsum board suspended ceilings and wall cladding systems with direct hangers as a frame component.

### Storage

- Profiles are tied and packed on pallets.
- Direct contact with water should be avoided.
- Packages should be stored in flat, dry and clean areas.

### Standards referred to

TS EN 14195

### Fields of Application

- Gypsum board suspended ceiling systems
- Wall cladding systems with direct hangers

## Technical Data

Description	Thickness (mm)	Weight (kg/m)	Width (mm)	Flange (mm)	Length (mm)	Packaging (pcs.)	Material Number
Knauf Ceiling U Channel	0,6	0,320	28	25/25	3000	12	133408
		0,384		27/27			147106

## System Performance Values

Performance values as sound insulation, fire resistance etc. may differ acc. to the drywall system to be applied. Please check the performance values of the drywall systems;

[Knauf Technical Website](#)  
[Document Center](#)

## Application

Application should be done acc. to the applicable standards and acc. to the Knauf Technical Brochures of the respective drywall system.

▶ 444 YAPI - 9274

▶ [www.knauf.com.tr](http://www.knauf.com.tr) / [www.teknik.knauf.com.tr](http://www.teknik.knauf.com.tr)

▶ [teknik@knauf.com](mailto:teknik@knauf.com)

Center: Knauf Moment Beştepe Office, Beştepe Mah. 32.Cadde No:1/212-218 06560 Beştepe-Yenimahalle  
/ ANKARA Tel: 0312 297 0100 Faks: 0312 266 4506