

Multi Pack (Ceiling Roll)

September 2025

Build on us.

Description

Multi Pack (Ceiling Roll) is a glass mineral wool roll that is non-combustible with a Euroclass A1 reaction to fire classification and is manufactured using our unique plant based binder ECOSE® Technology.

Multi Pack (Ceiling Roll) provides installers with flexibility of being used as a dual layer 100/150mm deep roll or as 2x50/2x75mm deep rolls. Rolls can easily be cut to suit joist centres.

Our advanced compression packaging technology ensures more insulation per pack, saving on transportation, storage space and reducing the amount of handling.

Benefits

- › Multi pack product that can be used between joists of various depths.
- › Non-combustible A1 Euroclass reaction to fire classification.
- › Lightweight quilt for ease of installation.
- › Compression packed for more efficient transportation and storage.
- › Manufactured with ECOSE® Technology for improved handling



NON-COMBUSTIBLE
INSULATION

with **ECOSE**[®]
TECHNOLOGY



Multi Pack (Ceiling Roll)

Technical Specifications

MULTI PACK (CEILING ROLL) 2X50MM

Thickness (mm)	R-value m ² K/W	Length (m)	Width (mm)	Pieces per pack	Area per pack (m ²)	Packs per pallet	Product Code
50	1.05	27.00	1200	1	32.40	24	633623
100	2.10	13.50	1200	1	16.20	24	633623

MULTI PACK (CEILING ROLL) 2X75MM

Thickness (mm)	R-value m ² K/W	Length (m)	Width (mm)	Pieces per pack	Area per pack (m ²)	Packs per pallet	Product Code
75	1.70	17.60	1200	1	21.12	24	866994
150	3.40	8.80	1200	1	10.56	24	866994

All dimensions are nominal



South African R-values calculated assuming 23°C mean temperature.

Multi Pack (Ceiling Roll)

Performance

FIRE CLASSIFICATION

A1	A2-s1, d0	B	C	D	E	F
----	-----------	---	---	---	---	---

Euroclass reaction to fire classification – in accordance to SANS 53501-1

VAPOUR RESISTIVITY

5.00 MNs/g.m

Certification, accreditations and industry standards




Applications



Cold roof - ceiling level

Typical Build-Ups



Multi Pack (Ceiling Roll)

Application

Multi Pack (Ceiling Roll) is used for the thermal insulation of pitched roofs at Ceiling level. Multi Pack (Ceiling Roll) can be installed as a single or dual layer. For dual layer installation, unroll the product and leave both layers together. For single layer installation, unroll the product and then turn over the top layer into the next set of joists.

Standards and Certification

Multi Pack (Ceiling Roll) has a product declaration made in conformity with the requirements of BS EN 13162:2012+A1:2015 and are manufactured in accordance with ISO 50001:2018 Energy Management Systems, ISO 14001:2015+A1:2024 Environmental Management Systems, ISO 45001:2023+A1 Occupational Health and Safety Management Systems, and ISO 9001:2015+A1:2024 Quality Management Systems.

All of our mineral wool products are made of non-classified fibres and are certified by EUCEB. EUCEB (European Certification Board of Mineral Wool Products - www.euceb.org) is a voluntary initiative by the mineral wool industry. It is an independent certification authority that guarantees that products are made of fibres which comply with the exoneration criteria for carcinogenicity (Note Q) of the Regulation (EC) 1272/2008.

Thermal Modelling

The U-value of a proprietary built element (rainscreen facade/ masonry cavity wall/garage soffit etc.) or system is dependent on the material properties and the degree of thermal bridging in the system.

Calculations should be created using 2D or 3D modelling programs which comply with the methodologies detailed in BS EN ISO 6946:2017 or BS EN ISO 10211:2017 and using guidance from BR443:2019.

We offer simplified calculations to BS EN ISO 6946:2017 and where required numerically modelled U-value calculations using software that is compliant with BS EN ISO 10211:2017.

System Testing

Knauf Insulation maintains declared product characteristics and qualities which are defined in detail in its Declaration of Performances (DoPs) and product literature. The product literature also includes information relating to Knauf Insulation's requirements and recommendations for installation of its products when being used as part of a system.

Any party using, or planning to use, our products in a system (with or without system testing) where performance may be dependent on product characteristics not declared on our DoPs or our product literature, must contact our Technical Services Team.

Knauf Insulation will not accept liability for any failure in system performance due to product characteristics not declared on DoPs or product literature, or not agreed in a Service Level Agreement. In such an event, any warranty given in relation to those products will be invalidated.

Real Performance

Glass and rock mineral wool are easier to install correctly than other insulants, such as rigid boards, because they adapt to any slight imperfections in the substrate and knit together, eliminating any air gaps. Mineral wool is engineered to adapt to any imperfections, and any settlement/movement over time, so it maintains close contact and preserves thermal performance for the life of the building.

Evidence shows the absence of air gaps is crucial to achieving real performance in the relevant application. Any insulation material that doesn't deliver 'as-built' thermal performance is failing in its primary purpose, and therefore presents an unnecessary risk as the construction industry seeks to close the performance gap.

Durability

Multi Pack (Ceiling Roll) is odourless, rot proof, non-hygroscopic, does not sustain vermin and will not encourage the growth of fungi, mould or bacteria.

Multi Pack (Ceiling Roll)

Sustainability

Multi Pack (Ceiling Roll) is manufactured with ECOSE® Technology, our unique plant-based binder which contains no added formaldehyde or phenol. It is made from natural raw materials that are rapidly renewable and is less energy-intensive to manufacture than traditional binders. Products made with ECOSE® Technology are soft to touch and easy to handle. They generate low levels of dust and VOCs and have been awarded the Eurofins Gold Certificate for Indoor Air Comfort.

All our glass mineral wool products have been awarded the DECLARE 'Red List Free' label. The Declare label is a third-party accreditation and is similar to a food nutrition label but for building products; it is a straightforward ingredient list and allows product transparency disclosure because it identifies where a product comes from and what it is made of. Declare 'Red List Free' certifies that there is no harmful chemical from the red list in these products.

Our glass mineral wool is made with up to 80% recycled content (incl. glass from windows, bottles and jars).

Multi Pack (Ceiling Roll) contains no ozone-depleting substances or greenhouse gases. The overall environmental performance of our products is reported in their EPDs (Environmental Product Declarations) which are available on our website. EPDs are available for all our products in accordance with ISO 14025:2023, ISO 21930:2017 and EN 15804+A2:2019.

We have received the BES6001(v4.0) 'Very Good' rating for all our mineral wool in our three plants, which proves that our products are made with constituent materials that are responsibly sourced.

Our 3-tier industry-leading compression-packaging technology allows us to load more product per pack or pallet, and therefore onto each truck that leaves our factories. This means less packaging used per m² of insulation, fewer vehicles on our roads, so less associated CO₂ emissions. It also means less transport, handling and storage space required for our customers.

Our individual products and the pallets they sit on are wrapped in low-density polyethylene (LDPE4) plastic, which is made of 30-50% (depending on the supplier) recycled plastic content and is fully recyclable.

Handling and Storage

Multi Pack (Ceiling Roll) should be stored properly and handled in such a way as to ensure that the product remains clean and undamaged.

The polythene packs / shrink-wrapped pallets used for the supply of Multi Pack (Ceiling Roll) are designed for short-term protection only. For longer term protection on site, the product should either be stored indoors or under cover and off the ground. Multi Pack (Ceiling Roll) should not be left permanently exposed to the elements.

If the main hood is removed or damaged, the remaining packs should be kept under cover indoors or protected from the elements by a weatherproof cover. In coastal locations where weather is more extreme and bird damage is more common, use additional covering or store indoors.

The product must be protected from prolonged exposure to sunlight and stored dry and flat.

Multi Pack (Ceiling Roll) is light and easy to handle; care should be exercised to avoid crushing their edges. If damaged, the product should be discarded. Damaged, contaminated or wet product must not be used.

During construction exposed areas of rolls should always be covered at the end of a day's work or in heavy rain. Polyethylene covers should be used to provide protection and prevent work from becoming saturated.

Knauf Insulation Ltd

Stafford Road, St.Helens, Merseyside, WA10 3LZ Enquiries: +27 647525029

All rights reserved, including those of photomechanical reproduction and storage in electronic media. Extreme caution was observed when putting together and processing the information, text and illustrations in this document. Nevertheless, errors cannot be completely ruled out. The publisher and editors cannot assume legal responsibility or any liability for incorrect information and consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of possible errors pointed out. For the most up-to-date document versions and product information, please always refer to our website.