


KNAUF

Armstrong Sierra OP























Sierra OP features unmatched sound absorption and a visually captivating smooth surface.

- White, laminated mineral tile with an appealing surface
- Excellent sound absorption
- High light reflectance
- ISO 5 Clean Room Performance
- Ideal for open plan offices, educational spaces, call centres (IT/ITeS), large conference rooms, theatres & auditoriums

Build on us.

Armstrong Sierra OP

Characteristic	Detailed information							
Edge details								
Thickness (mm)		15	15	15				
Dimensions (mm)		600 x 600	600 x 600	600 x 600				
System		Exposed Grid System, Demountable Ceiling (Prelude 24 mm)		Exposed Grid System, Demountable Ceiling (Suprafine 15 mm / Silhouette)				
Weight		≅ 2.4 kg/m²						
Colour		 White						
Sound attenuation		CAC = 25 dB						
Sound absorption		Frequency f (HZ)	125	250	500	1000	2000	4000
		a_p	0.50	0.75	0.90	0.85	1.00	1.00
		NRC = 0.90						
Fire reaction		A2-s1, d0 as per EN 13501-1						
Light reflectance		Up to 88%						
Thermal conductivity		$\lambda = 0.040 \text{ W/mK}$						
Humidity resistance		Up to 95% RH						
Recycled content		Up to 43%						
Clean room		ISO 5 (Class100)						
Cleanability								
Sustainability		