

TECH DATA

Benefits

- One 10mm board for wall and ceilings
- Can span 610mm centres on ceilings
- Sag resistant ceiling solution



SpanShield can be used in residential and commercial applications.

SpanShield is standard plasterboard made from a core of gypsum sandwiched between two layers of heavy duty recycled paper. The face paper is coloured ivory ready for paint or wall paper finish.

Application

SpanShield is an internal wall and ceiling lining suitable for residential and commercial applications. It is usually installed over a timber or steel

frame and can also be installed over a masonry wall.

Installation

SpanShield is usually installed using the 'Fastener and Stud Adhesive Method'. It may also be installed using the 'Fastener Only Method' or 'Masonry Adhesive Method'.

Refer to the Knauf *Plasterboard Installation Site* guide for complete installation instructions.

Product Information

STANDARD SHEET SIZE	THICKNESS (mm)	WIDTH (mm)	LENGTH (mm)	WEIGHT* (kg/m ²)
	10	1220	2440	7.0
FIRE HAZARD PROPERTIES	Group 1S material according to NZBC Performance Clause 3.4(a)			
VOLATILE ORGANIC COMPOUNDS	Less than 0.5mg/m TVOC			
HAZARDS IDENTIFICATION	Non hazardous			

* Weights indicated are nominal

SpanShield is manufactured in accordance with ASTM C1396

Technical Advice

For technical inquiries, please contact:

+639178996727

Knauf Gypsum Philippines, Inc.,

Pasig City Office: 14F – Office 2,
One Paseo Bldg., Paseo de Arco
Cor. E. Rodriguez Ave. (C5)
ArcoVia City, Pasig City, 1604
Philippines

+639178533593