



Knauf Ceiling C Channel

Profile

Product Description

Galvanized lightweight steel section for use in suspended ceilings as furring and main channels; and as main stud in wall lining systems with direct hangers.

Storage

- Profiles are tied and packed on pallets.
- Direct contact with water should be avoided.
- Packages should be stored in flat, dry and clean areas.

Standards referred to

TS EN 14195

Fields of Application

- Gypsum board suspended ceiling systems
- Wall cladding systems with direct hangers

Technical Data

Description	Thickness (mm)	Weight (kg/m)	Width (mm)	Flange (mm)	Length (mm)	Packaging (pcs.)	Material Number
Ceiling C Channel	0,6	0,580	60	27	3000	12	319198
Cross TC Channel							24599

System Performance Values

Performance values as sound insulation, fire resistance etc. may differ acc. to the drywall system to be applied. Please check the performance values of the drywall systems;

[Knauf Technical Website](#)
[Document Center](#)

Application

Application should be done acc. to the applicable standards and acc. to the Knauf Technical Brochures of the respective drywall system.

▶ 444 YAPI - 9274

▶ www.knauf.com.tr / www.teknik.knauf.com.tr

▶ teknik@knauf.com

Center: Knauf Moment Beştepe Office, Beştepe Mah. 32.Cadde No:1/212-218 06560 Beştepe-Yenimahalle
/ ANKARA Tel: 0312 297 0100 Faks: 0312 266 4506