



**TÜRK STANDARDLARI ENSTİTÜSÜ**  
**TÜRK STANDARDLARINA UYGUNLUK BELGESİ**  
**TURKISH STANDARDS INSTITUTION**  
**CERTIFICATE OF CONFORMITY TO TURKISH STANDARDS**

Markanın Tanımı Description of the Mark  
TSE veya/or  veya/or T S E

<b>BELGE NUMARASI</b> REFERENCE NUMBER OF LICENCE	001729-TSE-34/07
<b>BELGENİN İLK VERİLİŞ TARİHİ</b> DATE OF FIRST ISSUE OF LICENCE	05.12.2011
<b>BELGENİN SON GEÇERLİLİK TARİHİ</b> LICENCE VALID UNTIL	19.06.2025
<b>BELGE SAHİBİ KURULUŞUN ADI</b> NAME OF THE LICENCE HOLDER	KNAUF İNŞAAT VE YAPI ELEMANLARI SANAYİ VE TİCARET ANONİM ŞİRKETİ
<b>BELGE SAHİBİ KURULUŞUN ADRESİ</b> ADDRESS OF THE LICENCE HOLDER	BEŞTEPE MAH. 32 CAD. NO:1 /212 YENİMAHALLE ANKARA/TÜRKİYE
<b>ÜRETİM YERİ ADI</b> NAME OF THE MANUFACTURING PLACE	KNAUF İNŞAAT VE YAPI ELEMANLARI SANAYİ VE TİC. A.Ş.
<b>ÜRETİM YERİ ADRESİ</b> ADDRESS OF THE MANUFACTURING PLACE	AHİBOZ SERPMELER MEVKİİ NO:246 GÖLBAŞI ANKARA / TÜRKİYE
<b>İPTAL EDİLEN BELGE NUMARASI (Varsa)</b> INDICATION OF SUPERSEDED LICENCE (if any)	001729-TSE-34/06
<b>TESCİLLİ TİCARİ MARKASI</b> REGISTERED TRADE MARK	ALÇIPAN
<b>İLGİLİ TÜRK STANDARDI</b> RELATED TURKISH STANDARD	TS EN 520+A1 / 24.06.2010
<b>BELGE KAPSAMI</b> SCOPE OF LICENCE	

- 1)  
REACTION TO FIRE CLASS: A2-s1,d0  
WIDTH: 1200 MM  
LENGTH: 2000-4000 MM  
THICKNESS: 18 MM  
GYPSUM PLASTERBOARDS-TAPERED EDGE-SQUARE EDGE  
TYPE A  
COMMERCIAL MODEL: ALÇIPAN Herkül
- 2)  
REACTION TO FIRE CLASS: A2-s1,d0  
WIDTH: 1200 MM  
LENGTH: 2000-4000 MM  
THICKNESS: 18 MM

e-İmzalı/e-signed

17.07.2024

On Behalf Of The Head Of Certification Center  
ŞİMA AKKAYA  
DIRECTOR OF CONSTRUCTION MATERIALS  
SECTOR

\*This certificate also shows that the production place of the certified product meets the requirements of Institute.  
\*This certificate under any circumstances cannot be changed, duplicated partially or in a way that makes it difficult to read and erasure cannot be done.  
\*TSE CONSTRUCTION MATERIALS SECTOR DIRECTORATE \* Address: Necatibey Cad.No:112 06100 Bakanlıklar/ANKARA \* Telephone: 0312 416 63 79\* Fax: 0312-416 66 17  
\*TSE HEAD OF CERTIFICATION CENTER; Address: Necatibey Cad. No:112 06100 Bakanlıklar/ANKARA – Telephone: 0 312 416 64 81 / 416 64 27, Fax:0 312 416 66 17 E-mail :bmb@tse.org.tr , web : www.tse.org.tr





**TÜRK STANDARDLARI ENSTİTÜSÜ**  
**TÜRK STANDARDLARINA UYGUNLUK BELGESİ**  
**TURKISH STANDARDS INSTITUTION**  
**CERTIFICATE OF CONFORMITY TO TURKISH STANDARDS**

Markanın Tanımı Description of the Mark  
**TSE** veya/or  veya/or **T S E**

(001729-TSE-34/07 nolu belge devamı) : KNAUF İNŞAAT VE YAPI ELEMANLARI SANAYİ VE TİCARET ANONİM ŞİRKETİ  
İLGİLİ TÜRK STANDARDI (RELATED TURKISH STANDARD) TS EN 520+A1 / 24.06.2010

GYPSUM PLASTERBOARDS-TAPERED EDGE-SQUARE EDGE  
TYPE H2 (GYPSUM PLASTERBOARD WITH REDUCED WATER ABSORPTION RATE)  
COMMERCIAL MODEL: ALÇIPAN Herkül

3)  
REACTION TO FIRE CLASS: A2-s1,d0  
WIDTH: 1200 MM  
LENGTH: 2000-4000 MM

THICKNESS: 18 MM  
GYPSUM PLASTERBOARDS-TAPERED EDGE -SQUARE EDGE  
TYPE F (GYPSUM PLASTERBOARD WITH IMPROVED CORE ADHESION AT HIGH TEMPERATURE)  
COMMERCIAL MODEL: ALÇIPAN Herkül

4)  
REACTION TO FIRE CLASS: A2-s1,d0  
WIDTH: 1200 MM  
LENGTH: 2000-4000 MM  
THICKNESS: 18 MM

GYPSUM PLASTERBOARDS-TAPERED EDGE -SQUARE EDGE  
TYPE FH2 (GYPSUM PLASTERBOARD WITH IMPROVED CORE ADHESION AT HIGH TEMPERATURE AND REDUCED WATER ABSORPTION RATE)  
COMMERCIAL MODEL: ALÇIPAN Herkül

5)  
REACTION TO FIRE CLASS: A2-s1,d0  
WIDTH: 1200 MM  
LENGTH: 2000-4000 MM  
THICKNESS: 6,5 MM  
GYPSUM PLASTERBOARDS-SQUARE EDGE  
TYPE A  
COMMERCIAL MODEL: ALÇIPAN Herform (EXPANSION OF SCOPE:18.01.2018)

6)  
REACTION TO FIRE CLASS: A2-s1,d0  
WIDTH: 1200 MM  
LENGTH: 2000-4000 MM  
THICKNESS: 12,5 MM-15 MM

GYPSUM PLASTERBOARDS-TAPERED EDGE -SQUARE EDGE  
TYPE F (GYPSUM PLASTERBOARD WITH IMPROVED CORE ADHESION AT HIGH TEMPERATURE)  
COMMERCIAL MODEL: ALÇIPAN FR Yangına Dayanıklı (EXPANSION OF SCOPE:18.01.2018)

7)  
REACTION TO FIRE CLASS: A2-s1,d0  
WIDTH: 1200 MM  
LENGTH: 2000-4000 MM  
THICKNESS: 12,5-15 MM

*e-imzalı/e-signed*

17.07.2024

On Behalf Of The Head Of Certification Center  
ŞİMA AKKAYA

DIRECTOR OF CONSTRUCTION MATERIALS  
SECTOR

\*This certificate also shows that the production place of the certified product meets the requirements of Institute.

\*This certificate under any circumstances cannot be changed, duplicated partially or in a way that makes it difficult to read and erasure cannot be done.

\*TSE CONSTRUCTION MATERIALS SECTOR DIRECTORATE \* Address: Necatibey Cad.No:112 06100 Bakanlıklar/ANKARA \* Telephone: 0312 416 63 79\* Fax: 0312-416 66 17

\*TSE HEAD OF CERTIFICATION CENTER; Address: Necatibey Cad. No:112 06100 Bakanlıklar/ANKARA – Telephone: 0 312 416 64 81 / 416 64 27, Fax:0 312 416 66 17 E-mail : bmb@tse.org.tr , web : www.tse.org.tr





**TÜRK STANDARDLARI ENSTİTÜSÜ**  
**TÜRK STANDARDLARINA UYGUNLUK BELGESİ**  
**TURKISH STANDARDS INSTITUTION**  
**CERTIFICATE OF CONFORMITY TO TURKISH STANDARDS**

Markanın Tanımı Description of the Mark  
**TSE** veya/or  veya/or **TSE**

(001729-TSE-34/07nolu belge devamı) : KNAUF İNŞAAT VE YAPI ELEMANLARI SANAYİ VE TİCARET ANONİM ŞİRKETİ  
İLGİLİ TÜRK STANDARDI(RELATED TURKISH STANDARD) TS EN 520+A1 / 24.06.2010

GYPSUM PLASTERBOARDS-TAPERED EDGE-SQUARE EDGE  
TYPE DF (GYPSUM PLASTERBOARD WITH CONTROLLED DENSITY, IMPROVED CORE ADHESION AT HIGH TEMPERATURE)  
COMMERCIAL MODEL: ALÇIPAN FR Yangına Dayanımlı (EXPANSION OF SCOPE:18.01.2018)  
8)  
REACTION TO FIRE CLASS: A2-s1,d0  
WIDTH: 1200-1220 MM  
LENGTH: 2000-4000 MM  
THICKNESS: 8-9,5-12,5-15 MM  
GYPSUM PLASTERBOARDS-TAPERED EDGE-SQUARE EDGE  
TYPE A  
COMMERCIAL MODEL: ALÇIPAN FLEX (FX) (EXPANSION OF SCOPE:18.01.2018)  
9)  
REACTION TO FIRE CLASS: A2-s1,d0  
WIDTH: 1200 MM  
LENGTH: 2000-4000 MM  
THICKNESS: 12,5-15 MM  
GYPSUM PLASTERBOARDS-TAPERED EDGE  
TYPE A  
COMMERCIAL MODEL: Alçıpan 4 Pah (EXPANSION OF SCOPE:18.01.2018)  
10)  
REACTION TO FIRE CLASS: A2-s1,d0  
WIDTH: 1200 MM  
LENGTH: 2000-4000 MM  
THICKNESS: 12,5-15 MM  
GYPSUM PLASTERBOARDS-TAPERED EDGE-SQUARE EDGE  
TYPE FH2 (GYPSUM PLASTERBOARD WITH IMPROVED CORE ADHESION AT HIGH TEMPERATURE AND REDUCED WATER ABSORPTION RATE)  
COMMERCIAL MODEL: ALÇIPAN WR+FR Yangına ve Suya Dayanımlı (EXPANSION OF SCOPE:18.01.2018)  
11)  
REACTION TO FIRE CLASS: A2-s1,d0  
WIDTH: 1200 MM  
LENGTH: 2000-4000 MM  
THICKNESS: 9,5-12,5-15 MM  
GYPSUM PLASTERBOARDS-TAPERED EDGE-SQUARE EDGE  
TYPE H2 (GYPSUM PLASTERBOARD WITH REDUCED WATER ABSORPTION RATE)  
COMMERCIAL MODEL: ALÇIPAN WR Suya Dayanımlı (EXPANSION OF SCOPE:18.01.2018)  
12)  
REACTION TO FIRE CLASS: A2-s1,d0  
WIDTH: 1200 MM  
LENGTH: 2000-4000 MM

*e-İmzalı/e-signed*

17.07.2024

On Behalf Of The Head Of Certification Center  
ŞİMA AKKAYA  
DIRECTOR OF CONSTRUCTION MATERIALS  
SECTOR

\*This certificate also shows that the production place of the certified product meets the requirements of Institute.  
\*This certificate under any circumstances cannot be changed, duplicated partially or in a way that makes it difficult to read and erasure cannot be done.  
\*TSE CONSTRUCTION MATERIALS SECTOR DIRECTORATE \* Address: Necatibey Cad.No:112 06100 Bakanlıklar/ANKARA \* Telephone: 0312 416 63 79\* Fax: 0312-416 66 17  
\*TSE HEAD OF CERTIFICATION CENTER; Address: Necatibey Cad. No:112 06100 Bakanlıklar/ANKARA – Telephone: 0 312 416 64 81 / 416 64 27, Fax:0 312 416 66 17 E-mail :bmb@tse.org.tr , web : www.tse.org.tr





**TÜRK STANDARDLARI ENSTİTÜSÜ**  
**TÜRK STANDARDLARINA UYGUNLUK BELGESİ**  
**TURKISH STANDARDS INSTITUTION**  
**CERTIFICATE OF CONFORMITY TO TURKISH STANDARDS**



(001729-TSE-34/07 nolu belge devamı) : **KNAUF İNŞAAT VE YAPI ELEMANLARI SANAYİ VE TİCARET ANONİM ŞİRKETİ**  
İLGİLİ TÜRK STANDARDI(RELATED TURKISH STANDARD) TS EN 520+A1 / 24.06.2010

THICKNESS: 12,5-15 MM  
GYPSUM PLASTERBOARDS-TAPERED EDGE-SQUARE EDGE  
TYPE DFH2IR (GYPSUM PLASTERBOARD WITH CONTROLLED DENSITY, IMPROVED CORE ADHESION AT HIGH TEMPERATURE, REDUCED WATER ABSORPTION RATE, ENHANCED SURFACE HARDNESS AND ENHANCED STRENGTH )  
COMMERCIAL MODEL: Diamant (EXPANSION OF SCOPE:18.01.2018)  
13)  
REACTION TO FIRE CLASS: A2-s1,d0  
WIDTH: 1200 MM  
LENGHT: 2000-4000 MM  
THICKNESS: 12,5 MM  
GYPSUM PLASTERBOARDS-TAPERED EDGE-SQUARE EDGE  
TYPE H3 (GYPSUM PLASTERBOARD WITH REDUCED WATER ABSORPTION RATE)  
COMMERCIAL MODEL: ALÇIPAN WR Easy Suya Dayanıklı (EXPANSION OF SCOPE:18.06.2019)  
14)  
REACTION TO FIRE CLASS: A2-s1,d0  
WIDTH: 1200 MM  
LENGHT: 2000-4000 MM  
THICKNESS: 12,5 MM  
GYPSUM PLASTERBOARDS- TAPERED EDGE-SQUARE EDGE  
TYPE A  
COMMERCIAL MODEL: Alçıpan Flex Easy (FX Easy) (EXPANSION OF SCOPE:18.06.2019)

*e-ııızalı/e-signed*

17.07.2024

On Behalf Of The Head Of Certification Center  
**ŞİMA AKKAYA**  
DIRECTOR OF CONSTRUCTION MATERIALS  
SECTOR

\*This certificate also shows that the production place of the certified product meets the requirements of Institute.

\*This certificate under any circumstances cannot be changed, duplicated partially or in a way that makes it difficult to read and erasure cannot be done.

\*TSE CONSTRUCTION MATERIALS SECTOR DIRECTORATE \* Address: Necatibey Cad.No:112 06100 Bakanlıklar/ANKARA \* Telephone: 0312 416 63 79\* Fax: 0312-416 66 17

\*TSE HEAD OF CERTIFICATION CENTER; Address: Necatibey Cad. No:112 06100 Bakanlıklar/ANKARA – Telephone: 0 312 416 64 81 / 416 64 27, Fax:0 312 416 66 17 E-mail :bmb@tse.org.tr , web : www.tse.org.tr

