

KNAUF

HERADESIGN® Screws



© iCubesWire

Build on us.

- Rust-protected, universal dry-wall screws with countersunk head for fastening HERADESIGN® acoustic panels.
- Galvanized and available in in standard colours (white and beige).

Characteristics	Detailed information								
Product description	Rust-protected, universal dry-wall screws with countersunk head for fastening HERADESIGN® acoustic panels to wood and metal sub-constructions. Version with partial thread and Torx T20 - suitable for wall or profile thicknesses up to 0.6mm.								
	Maximum spacing: - 600 resp. 300mm - 625 resp. 312mm								
Technical data	Length / Ø (mm)	Surface/Colour	Wood			Metal CD-profile			Packaging unit (pcs./Carton)
			for panel thickness (mm)			for panel thickness (mm)			
			15	25	35	15	25	35	
	35 / 4.5	Galvanized	●			●	●		200
	35 c ¹⁾ / 4.5	White, beige	●			●	●		200
	50 / 4.5	Galvanized		●			●	●	200
	50 c ¹⁾ / 4.5	White, beige		●			●	●	200
	60 / 4.5	Galvanized			●				200
60 c ¹⁾ / 4.5	White, beige			●				200	
¹⁾ Screws painted white (similar to RAL 9010) or beige (Natural tone 13) - Usage class 1 and 2 as per EN 1995-1-1:2010-12, galvanised, yellow chromated, A2L as per DIN EN ISO 4042 - Specially hardened screws (500 HV 0.3) - Optimised tip form for use with metal profiles									
Delivery	In cartons. Only supplied in complete package units.								
Corrosion protection	Not suitable for indoor swimming pools and outdoor applications. Please contact your screw supplier or screw manufacturer for suitable corrosion protection of screws for applications in indoor swimming pools, underground car parks, roofed outdoor applications or other special uses.								