


KNAUF

Armstrong Dune[®] RH99



The popular Armstrong Dune[®] offers lightly textured and microperforated surface combined with good sound absorption and sound attenuation performance. It is available in a range of sizes and edge profiles and offers outstanding value.

- Features a microperforated, finely sanded surface to offer a smooth installed visual
- Good sound absorption: NRC 0.50
- Good light reflectance: 85%
- Ideal for offices, retail, education, healthcare, corridors and lobbies

Build on us.

Armstrong Dune® RH99

Characteristic	Detailed information							
Edge details		Board 	Tegular 24 	Tegular 15 BE 				
Thickness (mm)		16	16	16				
Dimensions (mm)		600 x 600 600 x 1200	600 x 600 600 x 1200	600 x 600 600 x 1200				
System		Exposed Grid System, Demountable Ceiling (Prelude 24 mm)		Exposed Grid System, Demountable Ceiling (Suprafine 15 mm / Silhouette)				
Weight		≅ 3.9kg/m²						
Colour		 White						
Sound attenuation		CAC = 33 dB						
Sound absorption		Frequency f (HZ)	125	250	500	1000	2000	4000
		α_p	0.31	0.33	0.57	0.70	0.46	0.35
		NRC = 0.50						
Fire Reaction		Class 0 / Class 1 as per BS 476 Pt - 6 & 7 Class A as per ASTM E-84						
Light reflectance		Up to 85%						
Thermal conductivity		$\lambda = \mathbf{0.052 - 0.057 W/mK}$						
Humidity resistance		Up to 99% RH						
Recycled content		Up to 38%						
Cleanability								
Sustainability								