

# KNAUF

## Knauf Fill & Finish 30 Premium

Knauf Fill & Finish 30 Premium is a fast setting (30 minute) multi purpose gypsum based compound for bedding tapes and beads, as well as finishing. For hand application. Up to a Q2 finish.

*Product-Data-Sheet*



### Areas of Application

For jointing gypsum boards. For bedding joint tapes and finishing joints by hand application only.

### Compliance Standards

EN13963. Type 3B

### Key Benefits

- 30 minute working time
- 9 month shelf life

**Build on us.**

Creation Date: 02/11/2023  
Revision Reference: 002  
Revision Date: 04/03/2025

**Performance Data**

Reaction to Fire (R2F)	Flexural Strength (F)	Dangerous Substances (DS)
A1	NPD	NPD

**Technical Information**

Colour	Weight (kg)	Approximate Coverage	Material Number
Off White	10	4.5m <sup>2</sup> per 10kg bag*	622329

\*Based on filling application to tapered edge board

## Sustainability

### Substances of very high Concern (SVHC)

At the time of publication, under REACH UK and REACH EU regulations this product contains no SVHC. For more information please consult the Safety Data Sheet.

## Storage and Handling

Store in a dry area, protected from frost, high temperature and exposure to direct sunlight. Storage and application temperature to be above 5°C.

## Packaging

Paper sack with an inner plastic layer for protection.

## Shelf Life/Service Life

9 months from the date of production, which is printed on the bag.

## Disposal/Repair

Dispose of contents/container in accordance with licensed collectors sorting instructions.

## Health & Safety

Use of protective gloves, glasses and a face mask is recommended due to dust. Avoid prolonged contact with the skin. Refer to the safety data sheet for more information.

## Application / Installation

Add the powder to cold, clean water (6.8L/10kg bag) in a suitable clean mixing container. Mix to workable consistency.

Once mixed, the product remains usable for 30 minutes. Paper Joint tape is recommended to be used and bedded with Knauf Knauf Fill & Finish 30 Premium, followed by a finishing coat once dry.

If sanding is required, at least 120 grit sandpaper is recommended. Once the jointing is completed and dry, a coat of Knauf Wallboard Primer should be applied before decoration. For detailed application advice, consult BS 8000-8 2023.

## Additional Documentation

[Declaration of Performance UKCA](#)

[Declaration of Performance CE](#)

[Safety Data Sheet](#)

Datasheet for indoor air quality available on request.

Product Accreditations:



Knauf UK GmbH Company Accreditations:



The information given in this publication is believed to be current and accurate as at the date of publication, but no warranty, express or implied is given. Updates will not be automatically issued © Copyright Knauf 2024

### Customer Service

UK Tel: 0800 521 050  
Eire Tel: 01 4620739  
Email: [cservice@knauf.com](mailto:cservice@knauf.com)

### Technical Service

Tel: 0800 521050 (option 2)  
Email: [technical-uk@knauf.com](mailto:technical-uk@knauf.com)  
(excluding public holidays)

### UK Address

Knauf  
Kemsley Fields Business Park  
Sittingbourne  
Kent ME9 8SR

### Ireland Address

Knauf  
87 Broomhill Road  
Tallaght  
Dublin 24  
D24 WR85

Creation Date: 02/11/2023  
Revision Reference: 002  
Revision Date: 04/03/2025