

KNAUF

HERADESIGN® Superfine Plus



© Bartosz Makowski

HERADESIGN® Superfine Plus is a two layer magnesite bonded wood wool acoustic ceiling and wall panel.

- Provides trickle protection
- Excellent sound absorption performance

Build on us.

Characteristics		Detailed information																																																																							
System		B2.1, B2.2																																																																							
Edge details		AK-01 Plus																																																																							
Dimensions (mm)		1200 x 600																																																																							
Thickness (mm)		40	50																																																																						
		15/25	25/25																																																																						
Weight (kg/m ²)		10.1	14.9																																																																						
Sound absorption		<table border="1"> <thead> <tr> <th rowspan="2">Thickness (mm)</th> <th rowspan="2">TCH (mm)</th> <th rowspan="2">HERADESIGN® Acoustic lining (mm)</th> <th rowspan="2">HERADESIGN® Acoustic lining (kg/m³)</th> <th colspan="6">Frequencies (Hz), α_p</th> <th colspan="2">Entire range</th> <th rowspan="2">Class</th> </tr> <tr> <th>125</th> <th>250</th> <th>500</th> <th>1000</th> <th>2000</th> <th>4000</th> <th>NRC</th> <th>α_w</th> </tr> </thead> <tbody> <tr> <td>15</td> <td>225</td> <td>25</td> <td>90</td> <td>0.60</td> <td>0.90</td> <td>0.95</td> <td>0.90</td> <td>0.80</td> <td>0.90</td> <td>0.90</td> <td>0.90</td> <td>A</td> </tr> <tr> <td>25</td> <td>225</td> <td>25</td> <td>90</td> <td>0.60</td> <td>0.95</td> <td>1.00</td> <td>0.95</td> <td>0.90</td> <td>1.00</td> <td>0.95</td> <td>0.95</td> <td>A</td> </tr> <tr> <td>25</td> <td>225</td> <td>40</td> <td>90</td> <td>0.65</td> <td>0.95</td> <td>1.00</td> <td>0.95</td> <td>0.90</td> <td>0.90</td> <td>0.95</td> <td>0.95</td> <td>A</td> </tr> </tbody> </table>	Thickness (mm)	TCH (mm)	HERADESIGN® Acoustic lining (mm)	HERADESIGN® Acoustic lining (kg/m ³)	Frequencies (Hz), α_p						Entire range		Class	125	250	500	1000	2000	4000	NRC	α_w	15	225	25	90	0.60	0.90	0.95	0.90	0.80	0.90	0.90	0.90	A	25	225	25	90	0.60	0.95	1.00	0.95	0.90	1.00	0.95	0.95	A	25	225	40	90	0.65	0.95	1.00	0.95	0.90	0.90	0.95	0.95	A											
							Thickness (mm)	TCH (mm)	HERADESIGN® Acoustic lining (mm)	HERADESIGN® Acoustic lining (kg/m ³)	Frequencies (Hz), α_p						Entire range		Class																																																						
			125	250	500	1000					2000	4000	NRC	α_w																																																											
			15	225	25	90	0.60	0.90	0.95	0.90	0.80	0.90	0.90	0.90	A																																																										
25	225	25	90	0.60	0.95	1.00	0.95	0.90	1.00	0.95	0.95	A																																																													
25	225	40	90	0.65	0.95	1.00	0.95	0.90	0.90	0.95	0.95	A																																																													
*Other acoustic performances can be achieved.																																																																									
Reaction to fire		Euroclass B-s1,d0																																																																							
Thermal resistance		15/25 0.80 m ² K/W	25/25 0.90 m ² K/W																																																																						
Humidity resistance		Suitable for rooms with a constant humidity of up to 90%.																																																																							
Application areas		A decorative and acoustically effective suspended ceiling and wall panel for use in interior spaces as well as roofed outdoor areas that are not directly exposed to environmental influences such as rain or pollutants.																																																																							
Installation		The installation of HERADESIGN® acoustic panels should take place during the last phase of the job, and in temperature and humidity controlled conditions. All building activities which create dust must be completed before the start of installation. Store the panels flat and protect against moisture and dirt. The packaging does not protect the products against rain. HERADESIGN® products should be installed in strict accordance with Knauf Ceiling Solutions installation and storage guidelines.																																																																							
Designation code		WW-EN 13168-L4W2-T2-S2-P2,TR5-CL3																																																																							
Special information		<ul style="list-style-type: none"> • Manufacturing tolerances in nominal dimensions: L4, W2, T2: ± 1mm, for lengths > 1250mm L4: ± 2mm • Maximum changes in dimension in standard climate 23° C/50 % relative humidity: ± 1 % 																																																																							
Cleanability																																																																									
Colours		<p>Standard colours</p> <p> Vario Design Colours</p> <p>White* Nature** Black*** Granite Steel Green Marble Copper Oak Brass Sandstone Concrete</p> <p>*similar to RAL 9010 **similar to RAL 1015 ***similar to RAL 9005</p> <p>• Other colours from popular RAL and NCS colour systems are available. • Deviations in colour and visual appearance may occur due to the rough fibre and panel surface.</p>																																																																							
Sustainability																																																																									