

# MSK and MSKP runner



## MSK-/MSKP runner for partitions EN 14195

Page: 1/1

03/2020

PRODUCT DATA					
CHARACTERISTIC		VALUE	UNIT		
Fire	Reaction to fire	A1	Incombustible		
Strength	Yield point	250	N/mm <sup>2</sup>		
Contents	Hazardous contents	NPD			
Surface	Zinc	100	g/m <sup>2</sup>		
Corrosion class		C1			
Measurements	Widths ± 0.5	45/70/95/120/145/160	mm		
	Thickness	0.46	mm		
	Length	±	+ 0 / - 3		
	Other - see drawing	±	1 mm		

### Areas of use

Runner with or without polyethylene. Can be slotted in to each other. 87° angle between the flange and the body. The runners have a flange height of 33 mm. For non-bearing constructions in buildings with plasterboard according to EN 520 or reprocessed products according to EN 14190.

Profiles produced according to EN 14195.

### Variants/sizes:

Runner MSK(P)  
45/70/95/120/145/160 mm

PROFILE DATA					
	t	h	A	I <sub>y</sub>	W <sub>y</sub>
Profile	mm	mm	mm <sup>2</sup>	mm <sup>4</sup>	mm <sup>3</sup>
MSK(P) 45	0,46	45	33,4	1,01 x 10 <sup>4</sup>	0,36 x 10 <sup>3</sup>
MSK(P) 70	0,46	70	43,9	2,84 x 10 <sup>4</sup>	0,68 x 10 <sup>3</sup>
MSK(P) 95	0,46	95	49,6	5,44 x 10 <sup>4</sup>	0,93 x 10 <sup>3</sup>
MSK(P) 120	0,46	120	54,4	9,07 x 10 <sup>4</sup>	1,19 x 10 <sup>3</sup>
MSK(P) 145	0,46	145	58,8	13,87 x 10 <sup>4</sup>	1,47 x 10 <sup>3</sup>
MSK(P) 160	0,46	160	61,2	17,27 x 10 <sup>4</sup>	1,64 x 10 <sup>3</sup>

Steel quality: S250GD+Z100

