



GIFAfloor Edge Strip

Knauf GIFAfloor Edge Strip is a mineral wool perimeter strip for use with all Knauf Flooring Systems.

Product-Data-Sheet



Areas of Application

To be used on the perimeter for Brio, Hugo and GIFA FHB systems to avoid sound bridges and contacts to reduce unwanted sound transfer.

Compliance Standards

This product does not have a harmonised standard to allow for CE marking and or designated standard to allow for UKCA marking.

Key Benefits

- Contributes, with Hugo, Brio and FHB, to achieve the system acoustic and fire performance.
- Non-combustible material
- Stable
- Quick and easy installation
- Resistant to deformation and ageing

Creation Date: 16/01/2026
Revision Reference: 001
Revision Date: 16/01/2026

Build on us.

Product Information**Product Data**

Height (mm)	Length (mm)	Thickness (mm)	Items per pack	Material Number
100	1200	12	50	450687
100	1200	12	100	108502

Technical Data

Description	GIFAfloor edge insulation strip MW	Unit	Standard
Reaction to Fire	Euroclass A1	class	EN 13501-1
Density	≥90	kg/m ³	EN 1602

Additional Information

Sustainability

Substances of Very High Concern (SVHC)

At the time of publication, under REACH UK and REACH EU regulations this product contains no SVHC. For more information please consult the Safety Data Sheet.

Volatile Organic Compound Content (VOC)

At the time of publication, under REACH UK and REACH EU regulations this product contains no VOCs. For more information please consult the Safety Data Sheet.

Storage and Handling

Store in a dry place.

Disposal & Repair

Disposal should be in accordance with local authority requirements. Recycle where possible.

Health & Safety

Use of protective gloves and safety glasses is recommended. Avoid contact with skin. Refer to the safety data sheet for more information.

Application / Installation

Mark the finished height of the screed and fix GIFAfloor Edge Strip with the top edge at least 5mm higher than the finished height.

Possible fixing of the GIFAfloor Edge Strip by stapling above or below the screed cross-section including covering or by gluing, e.g. with Knauf Uniflott.

Ensure that the GIFAfloor Edge Strip is laid without gaps.

Then lay the floor panel such as FHB, Hugo or Brio.

Only cut off the protruding part of the GIFAfloor Edge Strip once the top layer has been laid.

Additional Documentation

[Safety Data Sheet](#)

Knauf UK GmbH Company Accreditations:



The information given in this publication is believed to be current and accurate as at the date of publication, but no warranty, express or implied is given. Updates will not be automatically issued © Copyright Knauf 2026.

Customer Service

UK Tel: 0800 521 050
Eire Tel: 01 4620739
Email: cservice@knauf.com

Technical Service

Tel: 0800 521050 (option 2)
Email: technical-uk@knauf.com
(excluding public holidays)

UK Address

Knauf
Kemsley Fields Business Park
Sittingbourne
Kent ME9 8SR

Ireland Address

Knauf
87 Broomhill Road
Tallaght
Dublin 24
D24 WR85

Creation Date: 16/01/2026
Revision Reference: 001
Revision Date: 16/01/2026