

KNAUF

Colora Painted Ceiling Tile

For T-bar Ceiling System



Build on us.

Colora

General Information

For applying with Grid Ceiling System (T-Bar), has a shiny white appearance, easy to install, does not accumulate heat, strong, durable, and safe for health and environment. Best used as a ceiling in building, office, house, condominium, learning institute, exhibition hall, and etc.

Available in 3 types; Standard, Moisture Resistant, and Heat Resistant.


- Smooth surface, constant color on every tiles
- No paint over needed
- Has a good light reflection, less lighting needed
- Non hazardous



Product Information

Thickness (mm)	Width (mm)	Length (mm)	Weight/piece	Piece/pack
9	600	600	2.02	8

*Made to Order, please contact Knauf representative.



Instructions

Installed with T-Bar Metal Profile, and wearing a clean gloves during an installation is recommended.

Specification

Knauf Painted Ceiling Tile; Colora square edges, 9 mm thickness, size 600x600 mm, manufactured following the TIS 219-2552 standard. Able to add a special property like moisture resistant and heat resistant. Installed with T-Bar Metal Profile, produced from Zinc dipped steel, folded into T-shape, coated with matted white color, edge height at least 32 mm and has 24 mm wide surface. Along with T-Bar Metal Profile assembling accessories.

