

## AQUAPANEL® Cement Board Outdoor

The ideal substrate for exterior walls in ventilated or water-managed (directly-applied) systems. Also for façade renovations and exterior ceiling applications.

### Description

AQUAPANEL® Cement Board Outdoor is a robust, non-combustible building panel, made of aggregated Portland cement with coated glass fibre mesh embedded in back and front surfaces. It offers all the benefits of a dry panel system with the strength of brick and block.

The ends are cut square and edges are reinforced for extra strength (the EasyEdge®). The panel provides a solid base that withstands extreme weather conditions.

### Physical properties

Parameter	Units
Length (mm)	2,400
Width (mm)	1,200
Thickness (mm)	12.5
Weight (kg/m <sup>2</sup> )	Approx. 16
Dry bulk density (kg/m <sup>3</sup> ) according to EN 12467	1,150
Bending strength (MPa) according to EN 12467	≥7
pH-value	12
Thermal conductivity (W/mK) according to EN ISO 10456	0.35
Water vapour diffusion coefficient μ (-) according to EN ISO 12572	66
Min. bending radius (m)	3
Min. bending radius for 300 mm wide strip (m)	1
Building material class according to EN 13501	A1 non-combustible



### Application

AQUAPANEL® Cement Board Outdoor is used in exterior applications for walls and ceilings as a directly-applied (water-managed) or ventilated system.

Furthermore, AQUAPANEL® Cement Board Outdoor can also serve as a substrate for ceramic and other linings as well as thermal insulation composite systems (ETICS).

### Characteristics

- Alternative to brick and block-work
- Drylining for faster progress
- Weather and water-resistant
- Strong, robust, impact-resistant and non-combustible
- Can be cut to shape using “score and snap” technique
- Simple and easy to install
- Can be bent when dry - up to 1 meter bending radius



## Transportation and storage

Always carry boards upright using a board trolley or on a pallet using a forklift truck. When setting the boards down, make sure that corners and edges are not damaged.

The supporting surface must be able to carry the weight of the boards. A pallet of AQUAPANEL® Cement Board Outdoor applies a floor loading from about 900 to 1,750 kg (as delivered). AQUAPANEL® Cement Board Outdoor must be protected from the effects of moisture and weather before installation. Boards that have become damp must be dried on both sides before use. Allow time for the boards to acclimatize to the ambient temperature and moisture conditions before installation. The material, ambient air and background temperature must not be below +5°C.

## Method of delivery

Thickness (mm)	Width (mm) x Length (mm)	Boards/Pallet	Surface/Pallet	Weight / Pallet	Item Code
12.5	1,200 x 2,400	30 pieces	86.4 m <sup>2</sup>	1,328.4 kg	129866

### **Knauf Gypsum Philippines, Inc.**

**1 14th Floor – Office 2, One Paseo Building  
Paseo de Arco corner E. Rodriguez Jr. Avenue  
(C5), ArcoVia City, Pasig City, 1604 Philippines**

### **Contact**

**+ 0917 853 3593  
info.ph@knauf.com**

[www.knauf.com/en-PH](http://www.knauf.com/en-PH)



## AQUAPANEL®

AQUAPANEL® is a technologically advanced building system. Because it's a system, it involves clear step-by-step process from design idea to project completion. AQUAPANEL® cement board panels, accessories and services work in unison – you can be certain that your project will all come together as planned. AQUAPANEL® is a registered trademark.

All technical changes reserved. Only the current printed instructions are valid. Our warranty is expressly limited to our products in flawless condition. The constructional and structural properties and characteristic building physics of Knauf systems can solely be ensured with the exclusive use of Knauf system components, or other products expressly recommended by Knauf. All application quantities and delivery amounts are based on empirical data that are not easily transferable to other deviating areas. All rights reserved. All amendments, reprints and photocopies, including those of excerpts, require the express permission of Knauf Aquapanel GmbH & Co. KG, Zur Helle 11, 58638 Iserlohn, Germany.

## Handling and installation

AQUAPANEL® Cement Board Outdoor is attached to a vertical stud frame. The substructure should be selected according to the static requirements. Depending on these requirements, it is possible to use single or double-layer planking or a combination with other Knauf construction boards. All necessary accessories are available in the AQUAPANEL® accessory range.

Other proprietary jointing and render systems may be used in accordance with the respective manufacturer's installation guidelines, provided they are compatible with AQUAPANEL® Cement Board Outdoor and comply with applicable codes and standards.

### **Installation time - wall:**

- approx. 15 min/m<sup>2</sup> (including screws, joint tape and joint filler).

### **Installation time - ceiling:**

- approx. 18 min/m<sup>2</sup> (including screws, joint tape and joint filler).
- › Stud spacing Wall: 600 mm horizontal installation (according to the static requirements, smaller distances are necessary)
- › Ceiling: 300 mm