


KNAUF

Armstrong Classic Lite[®] RH99






Armstrong CLASSIC Lite offers a non-directional pin hole visual and excellent Light Reflectance.

- Non-directional pin hole visual saves installation time & wastage
- Superior humidity resistance: RH99
- Ideal for offices, retail, education, healthcare

Build on us.

Armstrong Classic Lite® RH99

Characteristic	Detailed information							
Edge details		Board 	Tegular 24 	Tegular 15 BE 				
Thickness (mm)		16	16	16				
Dimensions (mm)		600 x 600 600 x 1200	600 x 600 600 x 1200	600 x 600 600 x 1200				
System		Exposed Grid System, Demountable Ceiling (Prelude 24 mm)			Exposed Grid System, Demountable Ceiling (Suprafine 15 mm / Silhouette)			
Weight		≅ 3.1 kg/m²						
Colour		 White						
Sound attenuation		CAC = 33 dB						
Sound absorption		Frequency f (HZ)	125	250	500	1000	2000	4000
		α_p	0.41	0.32	0.53	0.79	0.65	0.40
		NRC = 0.55						
Fire Reaction		Class 0 / Class 1 as per BS 476 Pt - 6 & 7 Class A as per ASTM E-84						
Light reflectance		Up to 87%						
Thermal conductivity		λ = 0.052 - 0.057 W/mK						
Humidity resistance		Up to 99% RH						
Recycled content		Up to 32%						
Cleanability	 							
Sustainability	 							