

KNAUF

KNAUF TOP FINISH®

Film-forming
finishing coat



KNAUF TOP FINISH®

KNAUF TOP FINISH® is a film-forming finishing coat designed to achieve smooth and flawless interior surfaces. It can be applied to various substrates, including cement, highly absorbent smooth concrete, plasterboard, and plaster coatings.

Advantages

- Easy preparation
- Homogeneous and lump-free paste
- Easy to spread
- Good adhesion
- High coverage
- Uniform drying
- Smooth finish

Build on us.

KNAUF TOP FINISH® Enduit pelliculaire de finition



Application Tools

Manual Application :

- Rubber mixing tub
- Trowel
- Float

Mechanical Application :

- PFT RITMO POWERCOAT machine

Precautions for Use

- Plaster dust may irritate the respiratory tract and cause coughing or other issues.
- **In case of contact with eyes** : rinse immediately with clean water, remove contact lenses if possible, and continue rinsing. Consult a doctor if symptoms persist.
- **Disposal** : dispose of in accordance with applicable local, regional, national, and international regulations.

TECHNICAL CHARACTERISTICS AND APPLICATION

Field of Application

Knauf TOP FINISH is a film-forming finishing coat designed for the following substrates:

- Cement
- Highly absorbent smooth concrete
- Plaster coatings
- Raw plasterboard before painting or other coverings

Composition

Knauf TOP FINISH is a fine white powder, primarily composed of plaster and additives.

Application

Treatment of Specific Substrates

- Smooth concrete or non-powdery plaster coating: Apply Knauf Betokontakt.
- Highly absorbent substrate (aerated concrete): Apply Knauf Stuc-Primer.

Application of the Coating

1. Apply Knauf TOP FINISH using a metal trowel, in two successive layers.
2. Recommended thickness: approximately 1 mm per layer.

Technical Data

- Start of setting: > 110 min
- End of setting: > 140 min
- Mixing ratio: 0.8 L of water per 1 kg (i.e., 1.6 L of water per 20 kg)
- Fineness: 100 µm < 1%

Storage

- Shelf life: 4 months in a dry place, protected from moisture.
- Recommended storage:
 - On pallets
 - Isolated from the ground

Coverage

- 1 bag of 20 kg produces 26 liters of wet mortar.
- Applied at a thickness of 1 mm, it covers approximately 26 m² per bag.

Standards and Certifications

- Compliant with EN 13279-1 : 2008 standard



Head Office Oran

Knauf Plâtres SARL: Chemin de Wilaya No. 64, 31063 Benfréha, Gdyl, Oran, Algeria. P.O. Box No. 2 - 31024 Boufatis, Oran, Algeria.

Sales Department Algiers

OBP - Oriental Business Park 2, 3rd Floor, Algiers Business District, Bab Ezzouar 16042, Algiers, Algeria.

Sétif Office

Business Center, Park Mall, No. 1104, 11th Floor 19000, Sétif, Algeria.

www.knauf.com

Tel.: +213 [0] 41 76 34 70 to 83 Fax: +213 [0] 41 76 34 75

