

# KNAUF

## Knauf ProRoll Light

Knauf ProRoll Light is a roller applied ready-mixed finishing plaster, used as a finish on plasterboard or over ProRoll Max. Apply up to 3mm thick. Up to a Q4 finish.

*Product-Data-Sheet*



### Areas of Application

For use onto ProRoll Max or directly on to plasterboard

### Compliance Standards

EN13963:2014

### Key Benefits

- Tub designed to fit a standard 9 inch roller
- Ready-mixed for convenient application
- Ideal for covering existing textured surfaces

**Build on us.**

Creation Date: 27/11/2023  
Revision Reference: 003  
Revision Date: 04/03/2025

**Performance Data**

Reaction to Fire (R2F)	Flexural Strength (F)	Density (kg/L)	Dangerous Substances (DS)
A2-s1, d0	NPD	1-1.4	Pass

**Technical Information**

Colour	Weight (kg)	Coverage	Material Number
White	12.5	10m <sup>2</sup> per tub at 1mm thickness	593010

## Sustainability

### Substances of very high Concern (SVHC)

At the time of publication, under REACH UK and REACH EU regulations this product contains no SVHC. For more information please consult the Safety Data Sheet.

### Volatile Organic Compound Content (VOC)

<0.1% (<1 g/l).

## Storage and Handling

Handle in accordance with good health and safety practice. Store in cool, dry conditions and keep sealed when not in use. 12 month shelf life when stored correctly. Not to be used below 10°C.

## Packaging

>30% Recycled plastic tub with a steel handle, packaged on a wooden pallet with PE shrink wrap

## Shelf Life/Service Life

12 months from the date of production, which is printed on the tub.

## Disposal/Repair

Ensure container is empty before disposing. Dispose in accordance with local authority requirements for plastic containers.

## Health & Safety

Wear suitable safety glasses with side shields due to risk of splashing, gloves to protect hands, and a dust mask when sanding.

## Application / Installation

Apply with a medium pile 9 inch roller at a thickness of up to 1mm, and smooth with a wide spatula. To achieve the perfect smooth finish, a second skimming coat can be applied after drying. Maximum 3mm thickness for 3 layers. Drying time approximately 12-18 hours per layer, which varies according to thickness, humidity and temperature. May be used as a finishing coat on ProRoll Max.

## Additional Documentation

[Declaration of Performance UKCA](#)

[Declaration of Performance CE](#)

[Safety Data Sheet](#)

Product Accreditations:



Knauf UK GmbH Company Accreditations:



The information given in this publication is believed to be current and accurate as at the date of publication, but no warranty, express or implied is given. Updates will not be automatically issued © Copyright Knauf 2024

### Customer Service

UK Tel: 0800 521 050  
Eire Tel: 01 4620739  
Email: [cservice@knauf.com](mailto:cservice@knauf.com)

### Technical Service

Tel: 0800 521050 (option 2)  
Email: [technical-uk@knauf.com](mailto:technical-uk@knauf.com)  
(excluding public holidays)

### UK Address

Knauf  
Kemsley Fields Business Park  
Sittingbourne  
Kent ME9 8SR

### Ireland Address

Knauf  
87 Broomhill Road  
Tallaght  
Dublin 24  
D24 WR85

Creation Date: 27/11/2023  
Revision Reference: 003  
Revision Date: 04/03/2025