



**TÜRK STANDARDLARI ENSTİTÜSÜ**  
**TÜRK STANDARDLARINA UYGUNLUK BELGESİ**  
**TURKISH STANDARDS INSTITUTION**  
**CERTIFICATE OF CONFORMITY TO TURKISH STANDARDS**

Markanın Tanımı Description of the Mark  
TSE veya/or  veya/or T S E

<b>BELGE NUMARASI</b> REFERENCE NUMBER OF LICENCE	001729-TSE-13/06
<b>BELGENİN İLK VERİLİŞ TARİHİ</b> DATE OF FIRST ISSUE OF LICENCE	23.04.2007
<b>BELGENİN SON GEÇERLİLİK TARİHİ</b> LICENCE VALID UNTIL	24.04.2025
<b>BELGE SAHİBİ KURULUŞUN ADI</b> NAME OF THE LICENCE HOLDER	KNAUF İNŞAAT VE YAPI ELEMANLARI SANAYİ VE TİCARET ANONİM ŞİRKETİ
<b>BELGE SAHİBİ KURULUŞUN ADRESİ</b> ADDRESS OF THE LICENCE HOLDER	BEŞTEPE MAH. 32 CAD. NO:1 /212 YENİMAHALLE ANKARA/TÜRKİYE
<b>ÜRETİM YERİ ADI</b> NAME OF THE MANUFACTURING PLACE	KNAUF İNŞAAT VE YAPI ELEMANLARI SAN. TİC.A.Ş.
<b>ÜRETİM YERİ ADRESİ</b> ADDRESS OF THE MANUFACTURING PLACE	KULLAR MEVKİİ OVACIK MAH.ÇULHANE CAD. KULLAR KOCAELİ / TÜRKİYE
<b>İPTAL EDİLEN BELGE NUMARASI (Varsa)</b> INDICATION OF SUPERSEDED LICENCE (if any)	001729-TSE-13/05
<b>TESCİLLİ TİCARİ MARKASI</b> REGISTERED TRADE MARK	ALÇIPAN
<b>İLGİLİ TÜRK STANDARDI</b> RELATED TURKISH STANDARD	TS EN 520+A1 / 24.06.2010
<b>BELGE KAPSAMI</b> SCOPE OF LICENCE	

- 1-  
REACTION TO FIRE CLASS: A2-s1,d0  
WIDTH: 1200 -1225 MM  
LENGHT: 2000-4000 MM  
THICKNESS: 12,5-15 MM  
GYPSUM PLASTERBOARDS-TAPERED EDGE  
TYPE H1 (GYPSUM PLASTERBOARD WITH REDUCED WATER ABSORPTION RATE)  
COMMERCIAL MODEL: ALÇIPAN MWR Küfe ve Suya Dayanıklı
- 2-  
REACTION TO FIRE CLASS: A2-s1,d0  
WIDTH: 1200 -1225 MM  
LENGHT: 2000-4000 MM  
THICKNESS: 9,5-12,5-15 MM

e-İmza/e-signed

12.03.2024

On Behalf Of The Head Of Certification Center  
ŞİMA AKKAYA

DIRECTOR OF CONSTRUCTION MATERIALS  
SECTOR

\*This certificate also shows that the production place of the certified product meets the requirements of Institute.  
\*This certificate under any circumstances cannot be changed, duplicated partially or in a way that makes it difficult to read and erasure cannot be done.  
\*TSE CONSTRUCTION MATERIALS SECTOR DIRECTORATE \* Address: Necatibey Cad.No:112 06100 Bakanlıklar/ANKARA \* Telephone: 0312 416 63 79\* Fax: 0312-416 66 17  
\*TSE HEAD OF CERTIFICATION CENTER; Address: Necatibey Cad. No:112 06100 Bakanlıklar/ANKARA – Telephone: 0 312 416 64 81 / 416 64 27, Fax:0 312 416 66 17 E-mail : bmb@tse.org.tr , web : www.tse.org.tr





**TÜRK STANDARDLARI ENSTİTÜSÜ**  
**TÜRK STANDARDLARINA UYGUNLUK BELGESİ**  
**TURKISH STANDARDS INSTITUTION**  
**CERTIFICATE OF CONFORMITY TO TURKISH STANDARDS**

Markanın Tanımı Description of the Mark  
**TSE** veya/or  veya/or 

(001729-TSE-13/06nolu belge devamı) : **KNAUF İNŞAAT VE YAPI ELEMANLARI SANAYİ VE TİCARET ANONİM ŞİRKETİ**  
İLGİLİ TÜRK STANDARDI(RELATED TURKISH STANDARD) TS EN 520+A1 / 24.06.2010

GYPSUM PLASTERBOARDS-TAPERED EDGE -SQUARE EDGE  
TYPE F (GYPSUM PLASTERBOARD WITH IMPROVED CORE ADHESION AT HIGH TEMPERATURE)  
COMMERCIAL MODEL: ALÇIPAN FR Yangına Dayanıklı

3-  
REACTION TO FIRE CLASS: A2-s1,d0

WIDTH: 1200 -1225 MM  
LENGHT: 2000-4000 MM  
THICKNESS: 12,5-15 MM

GYPSUM PLASTERBOARDS-TAPERED EDGE  
TYPE FH1 (GYPSUM PLASTERBOARD WITH IMPROVED CORE ADHESION AT HIGH TEMPERATURE AND  
REDUCED WATER ABSORPTION RATE)  
COMMERCIAL MODEL: ALÇIPAN MWFR Küfe, Suya ve Yangına Dayanıklı

4-  
REACTION TO FIRE CLASS: A2-s1,d0

WIDTH: 1200 -1225 MM  
LENGHT: 2000-4000 MM  
THICKNESS: 8-9,5-12,5-15 MM

GYPSUM PLASTERBOARDS-TAPERED EDGE-SQUARE EDGE  
TYPE A  
COMMERCIAL MODEL: ALÇIPAN FLEX (FX)

5-  
REACTION TO FIRE CLASS: A2-s1,d0

WIDTH: 1200 -1225 MM  
LENGHT: 2000-4000 MM  
THICKNESS: 9,5-12,5-15 MM

GYPSUM PLASTERBOARDS-TAPERED EDGE-SQUARE EDGE  
TYPE FH1 (GYPSUM PLASTERBOARD WITH IMPROVED CORE ADHESION AT HIGH TEMPERATURE AND  
REDUCED WATER ABSORPTION RATE)  
COMMERCIAL MODEL: ALÇIPAN WR+FR Yangına ve Suya Dayanıklı

6-  
REACTION TO FIRE CLASS: A2-s1,d0

WIDTH: 1200 -1225 MM  
LENGHT: 2000-4000 MM  
THICKNESS: 9,5-12,5-15 MM

GYPSUM PLASTERBOARDS-TAPERED EDGE-SQUARE EDGE  
TYPE FH2 (GYPSUM PLASTERBOARD WITH IMPROVED CORE ADHESION AT HIGH TEMPERATURE AND  
REDUCED WATER ABSORPTION RATE)  
COMMERCIAL MODEL: ALÇIPAN WR+FR Yangına ve Suya Dayanıklı

7-  
REACTION TO FIRE CLASS: A2-s1,d0

WIDTH: 1200 -1225 MM

e-*imzalı*/e-signed

12.03.2024

On Behalf Of The Head Of Certification Center  
**ŞİMA AKKAYA**

DIRECTOR OF CONSTRUCTION MATERIALS  
SECTOR

\*This certificate also shows that the production place of the certified product meets the requirements of Institute.

\*This certificate under any circumstances cannot be changed, duplicated partially or in a way that makes it difficult to read and erasure cannot be done.

\*TSE CONSTRUCTION MATERIALS SECTOR DIRECTORATE \* Address: Necatibey Cad.No:112 06100 Bakanlıklar/ANKARA \* Telephone: 0312 416 63 79\* Fax: 0312-416 66 17

\*TSE HEAD OF CERTIFICATION CENTER; Address: Necatibey Cad. No:112 06100 Bakanlıklar/ANKARA – Telephone: 0 312 416 64 81 / 416 64 27, Fax:0 312 416 66 17 E-mail : bmb@tse.org.tr , web : www.tse.org.tr





**TÜRK STANDARDLARI ENSTİTÜSÜ**  
**TÜRK STANDARDLARINA UYGUNLUK BELGESİ**  
**TURKISH STANDARDS INSTITUTION**  
**CERTIFICATE OF CONFORMITY TO TURKISH STANDARDS**

Markanın Tanımı Description of the Mark  
**TSE** veya/or  veya/or **T S E**

(001729-TSE-13/06nolu belge devamı) : **KNAUF İNŞAAT VE YAPI ELEMANLARI SANAYİ VE TİCARET ANONİM ŞİRKETİ**  
İLGİLİ TÜRK STANDARDI(RELATED TURKISH STANDARD) TS EN 520+A1 / 24.06.2010

LENGHT: 2000-4000 MM  
THICKNESS: 9,5-12,5-15 MM  
GYPSUM PLASTERBOARDS-TAPERED EDGE-SQUARE EDGE  
TYPE H1 (GYPSUM PLASTERBOARD WITH REDUCED WATER ABSORPTION RATE)  
COMMERCIAL MODEL: ALÇIPAN WR Suya Dayanıklı  
8-  
REACTION TO FIRE CLASS: A2-s1,d0  
WIDTH: 1200 -1225 MM  
LENGHT: 2000-4000 MM  
THICKNESS: 9,5-12,5-15 MM  
GYPSUM PLASTERBOARDS-TAPERED EDGE-SQUARE EDGE  
TYPE H2 (GYPSUM PLASTERBOARD WITH REDUCED WATER ABSORPTION RATE)  
COMMERCIAL MODEL: ALÇIPAN WR Suya Dayanıklı  
9-  
REACTION TO FIRE CLASS: A2-s1,d0  
WIDTH: 1200 -1225 MM  
LENGHT: 2000-4000 MM  
THICKNESS: 12,5 MM  
GYPSUM PLASTERBOARDS-TAPERED EDGE-SQUARE EDGE  
TYPE H3 (GYPSUM PLASTERBOARD WITH REDUCED WATER ABSORPTION RATE)  
COMMERCIAL MODEL: ALÇIPAN WR Suya Dayanıklı  
10-  
REACTION TO FIRE CLASS: A2-s1,d0  
WIDTH: 1200 -1225 MM  
LENGHT: 2000-3000 MM  
THICKNESS: 12,5-15 MM  
GYPSUM PLASTERBOARDS-TAPERED EDGE-SQUARE EDGE  
TYPE DFH2IR (GYPSUM PLASTERBOARD WITH CONTROLLED DENSITY, IMPROVED CORE ADHESION AT HIGH TEMPERATURE, REDUCED WATER ABSORPTION RATE, ENHANCED SURFACE HARDNESS AND ENHANCED STRENGTH )  
COMMERCIAL MODEL: Diamant  
11-  
REACTION TO FIRE CLASS: A2-s1,d0  
WIDTH: 1200 -1225 MM  
LENGHT: 2000-4000 MM  
THICKNESS: 12,5-15 MM  
GYPSUM PLASTERBOARDS-TAPERED EDGE-SQUARE EDGE  
TYPE A  
COMMERCIAL MODEL: ALÇIPAN Regular PLUS (K.G: 29.09.2020)  
12)  
REACTION TO FIRE CLASS: A2-s1,d0

e-imzalı/e-signed

12.03.2024

On Behalf Of The Head Of Certification Center  
ŞİMA AKKAYA

DIRECTOR OF CONSTRUCTION MATERIALS  
SECTOR

\*This certificate also shows that the production place of the certified product meets the requirements of Institute.

\*This certificate under any circumstances cannot be changed, duplicated partially or in a way that makes it difficult to read and erasure cannot be done.

\*TSE CONSTRUCTION MATERIALS SECTOR DIRECTORATE \* Address: Necatibey Cad.No:112 06100 Bakanlıklar/ANKARA \* Telephone: 0312 416 63 79\* Fax: 0312-416 66 17

\*TSE HEAD OF CERTIFICATION CENTER; Address: Necatibey Cad. No:112 06100 Bakanlıklar/ANKARA – Telephone: 0 312 416 64 81 / 416 64 27, Fax:0 312 416 66 17 E-mail : bmb@tse.org.tr , web : www.tse.org.tr





**TÜRK STANDARDLARI ENSTİTÜSÜ**  
**TÜRK STANDARDLARINA UYGUNLUK BELGESİ**  
**TURKISH STANDARDS INSTITUTION**  
**CERTIFICATE OF CONFORMITY TO TURKISH STANDARDS**

Markanın Tanımı Description of the Mark  
**TSE** veya/or  veya/or **T S E**

(001729-TSE-13/06nolu belge devamı) : KNAUF İNŞAAT VE YAPI ELEMANLARI SANAYİ VE TİCARET ANONİM  
ŞİRKETİ  
İLGİLİ TÜRK STANDARDI(RELATED TURKISH STANDARD) TS EN 520+A1 / 24.06.2010

WIDTH: 1200 MM  
LENGHT: 2500 MM  
THICKNESS: 12,5 MM  
GYPSUM PLASTERBOARDS-TAPERED EDGE-SQUARE EDGE  
TYPE DIR (GYPSUM PLASTERBOARD WITH CONTROLLED DENSITY, ENHANCED SURFACE HARDNESS AND STRENGTH)  
COMMERCIAL MODEL: ALÇIPAN FLEX(FX) ULTRA (KG:14.09.2021)  
13)  
REACTION TO FIRE CLASS: A2-s1,d0  
WIDTH: 1200 MM  
LENGHT: 2500 MM  
THICKNESS: 15 MM  
GYPSUM PLASTERBOARDS-TAPERED EDGE-SQUARE EDGE  
TYPE DIR (GYPSUM PLASTERBOARD WITH CONTROLLED DENSITY, ENHANCED SURFACE HARDNESS AND STRENGTH)  
COMMERCIAL MODEL: ALÇIPAN FLEX(FX) ULTRA (KG:14.09.2021)

*e-imzalı/e-signed*

12.03.2024

On Behalf Of The Head Of Certification Center  
ŞİMA AKKAYA

DIRECTOR OF CONSTRUCTION MATERIALS  
SECTOR

\*This certificate also shows that the production place of the certified product meets the requirements of Institute.

\*This certificate under any circumstances cannot be changed, duplicated partially or in a way that makes it difficult to read and erasure cannot be done.

\*TSE CONSTRUCTION MATERIALS SECTOR DIRECTORATE \* Address: Necatibey Cad.No:112 06100 Bakanlıklar/ANKARA \* Telephone: 0312 416 63 79\* Fax: 0312-416 66 17

\*TSE HEAD OF CERTIFICATION CENTER; Address: Necatibey Cad. No:112 06100 Bakanlıklar/ANKARA – Telephone: 0 312 416 64 81 / 416 64 27, Fax:0 312 416 66 17 E-mail :bmb@tse.org.tr , web : www.tse.org.tr

