



KNAUF SHEETROCK® VINYL 9.5MM & 12.5MM CEILING TILES

Knauf Sheetrock® Vinyl Ceiling Tiles come with reinforced plasterboard core and are finished with a very high-quality PVC lining that provides a durable face that is easy to clean.

knauf

Build on us.

Standard Specifications

Features & Benefits

- Easy to clean (Wipe with damp cloth)
- Excellent light reflectance
- Lightweight and easy to install

Texture – Capricorn



Applications

- Hospitals
- Laboratories
- Data rooms
- Kitchen and food preparation areas

Installation

Each piece of gypsum ceiling tile shall be installed following the same text direction at the back of the board to ensure design uniformity and colour consistency.

Product Enhancement

Protective Backing

Vinyl ceiling tiles can be provided with special backing on the reverse side upon request.



Aluminium Foil

Aluminium foil backing is designed for use in areas with extremely high temperatures.

Product Data

Thickness	9.5mm	12.5mm
Weight (kg/m ²)	5.7	7.6
Edge Details	Square 	
T-Bar Grid Size	Metric 600mm x 600mm 600mm x 1200mm	
	Imperial 610mm x 610mm 610mm x 1220mm	
Board Size	Metric 595mm x 595mm 595mm x 1195mm	
	Imperial 603mm x 603mm 603mm x 1212mm	
Product Testing	Base material of gypsum ceiling tiles are tested under BS 476 Part 6 and BS 476 Part 7	
Lamination Option	• Single side laminate (front)	

The above specifications are standard dimensions. Knauf is able to produce customised product lengths to suit specific project requirements. Terms and conditions apply.



Knauf Singapore Pte. Ltd.

79 Anson Road #07-01 Singapore 079906

T: (65) 6272 9272 E: contact-us.sg@knauf.com W: www.knauf.com

© 2024 KNAUF. All rights reserved. KNAUF and VINYL are trademarks of Knauf Singapore Pte. Ltd. or one or more of its affiliates. SHEETROCK is a trademark owned by United States Gypsum Company and used under license. Information provided is for reference purpose only. Due care has been taken to ensure accuracy at time of publication. Products, specifications, and requirements may vary according to geographical locations and applications. As each project is unique, please contact your nearest Knauf representative for further assessment.

Scan to visit
our website



SG_GCT03_FL_0824_V4 P_SG_GCT03_0824_01